ISO 15630-3:2019 (E)

Steel for the reinforcement and prestressing of concrete — Test methods — Part 3: Prestressing steel

Contents

Foreword

Introduction

- 1 Scope
- 2 Normative references
- 3 Terms, definitions and symbols
- 4 General provisions concerning test pieces
- 5 Tensile test
 - 5.1 Test piece
 - 5.2 Test equipment
 - 5.3 Test procedure
 - 5.3.1 General
 - 5.3.2 Determination of the modulus of elasticity
- 6 Bend test
 - 6.1 Test piece
 - 6.2 Test equipment
 - 6.3 Test procedure
 - 6.4 Interpretation of test results

7 Reverse bend test

- 7.1 Test piece
- 7.2 Test equipment
- 7.3 Test procedure

8 Wrapping test

- 8.1 Test piece
- 8.2 Test equipment
- 8.3 Test procedure
- 9 Isothermal stress relaxation test
 - 9.1 Principle of test
 - 9.2 Test piece
 - 9.3 Test equipment
 - 9.3.1 Frame
 - 9.3.2 Force-measuring device
 - 9.3.3 Length-measuring device (extensometer)
 - 9.3.4 Anchoring device
 - 9.3.5 Loading device
 - 9.4 Test procedure
 - 9.4.1 Provisions concerning the test piece
 - 9.4.2 Application of force
 - 9.4.3 Initial force
 - 9.4.4 Force during the test
 - 9.4.5 Maintenance of strain
 - 9.4.6 Temperature
 - 9.4.7 Frequency of force recording
 - 9.4.8 Frequency of strain recording

- 9.4.9 Duration of the test
- 10 Axial force fatigue test
 - 10.1 Principle of test
 - 10.2 Test piece
 - 10.3 Test equipment
 - 10.4 Test procedure
 - 10.4.1 Provisions concerning the test piece
 - 10.4.2 Stability of force and frequency
 - 10.4.3 Counting of force cycles
 - 10.4.4 Frequency
 - 10.4.5 Temperature
 - 10.4.6 Validity of the test

11 Stress corrosion test in a solution of thiocyanate

- 11.1 Principle of test
- 11.2 Sample and test piece
- 11.3 Test equipment
- 11.3.1 Frame
- 11.3.2 Force-measuring device
- 11.3.3 Time-measuring device
- 11.3.4 Test cell containing the test solution
- 11.3.5 Test solution
- 11.4 Test procedure
- 11.4.1 Provisions concerning the test pieces
- 11.4.2 Application and maintenance of force
- 11.4.3 Filling of the test cell
- 11.4.4 Temperature during the test
- 11.4.5 Termination of the test
- 11.4.6 Determination of median lifetime to fracture

12 Deflected tensile test

- 12.1 Principle of test
- 12.2 Sample and test pieces
- 12.3 Test equipment
- 12.3.1 General description
- 12.3.2 Dimensions
- 12.3.3 Anchorages
- 12.3.4 Mandrel
- 12.3.5 Loading device
- 12.4 Test procedure
- 13 Chemical analysis

14 Measurement of the geometrical characteristics

- 14.1 Test piece
- 14.2 Test equipment
- 14.3 Test procedures
- 14.3.1 Rib measurements
- 14.3.1.1 Height at the highest point (amax)
- 14.3.1.2 Rib height at a given position
- 14.3.1.3 Rib spacing (c)
- 14.3.1.4 Part of the circumference without ribs (∑ei)
- 14.3.1.5 Rib inclination angle (β)
- 14.3.1.6 Width of transverse rib (b)
- 14.3.2 Indentation measurements
- 14.3.2.1 General
- 14.3.2.2 Depth at the deepest point (amax)
- 14.3.2.3 Indentation spacing (c)
- 14.3.2.4 Length of indentation (I)
- 14.3.2.5 Part of the circumference without indentations (∑ei)
- 14.3.2.6 Indentation angle (β)
- 14.3.3 Lay length of strand (P)
- 14.3.4 Straightness

- 15 Determination of the relative rib area (fR)
 - 15.1 General
 - 15.2 Calculation of fR
 - 15.2.1 Relative rib area
 - 15.2.2 Simplified formulae
 - 15.2.3 Formula used for the calculation of fR
- 16 Determination of deviation from nominal mass per metre
 - 16.1 Test piece
 - 16.2 Accuracy of measurement
 - 16.3 Test procedure
- 17 Test report
- Annex A (informative) Options for agreement between the parties involved

Page count: 29