

ISO 4992-2:2020-03 (E)

Steel castings - Ultrasonic testing - Part 2: Steel I castings for highly stressed components

Contents		Page
Foreword		iv
1 Scope	1	1
2 Normative references		1
3 Terms and definitions		2
4 Requirements		3
4.1 Order information		3
4.2 Extent of testing		3
4.3 Maximum acceptable size of discontinuities		3
4.3.1 General		3
4.3.2 Indications without measurable dimensions		3
4.3.3 Indications with measurable dimensions		3
4.4 Qualification of personnel		5
4.5 Wall-section zones		5
4.6 Classes		5
5 Testing		5
5.1 Principles		5
5.2 Material		5
5.3 Test equipment, coupling fluid, test sensitivity and resolution of detection		6
5.3.1 Ultrasonic instrument		6
5.3.2 Probes and transducer frequencies		6
5.3.3 Checking of the ultrasonic test equipment		6
5.3.4 Coupling fluid		6
5.3.5 Test sensitivity and resolution of detection		7
5.4 Preparation of casting surfaces for testing		7
5.5 Test procedure		7
5.5.1 General		7
5.5.2 Range setting		8
5.5.3 Sensitivity setting		8
5.5.4 Consideration of various types of indications		9
5.5.5 Recording and recording limits		9
5.5.6 Assessment of indications to be recorded		9
5.5.7 Characterization and sizing of discontinuities		10
5.6 Test report		10
Annex A (normative) Resolution of detection of the instrument-probe combination	18	18
Annex B (informative) Sound-beam diameters	19	19
Annex C (informative) Types of indications generated by typical discontinuities	21	21
Bibliography	33	33