

ISO 4992-2:2020-03 (E)

Steel castings - Ultrasonic testing - Part 2: Steel castings for highly stressed components

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Requirements	3
4.1	Order information	3
4.2	Extent of testing	3
4.3	Maximum acceptable size of discontinuities	3
4.3.1	General	3
4.3.2	Indications without measurable dimensions	3
4.3.3	Indications with measurable dimensions	3
4.4	Qualification of personnel	5
4.5	Wall-section zones	5
4.6	Classes	5
5	Testing	5
5.1	Principles	5
5.2	Material	5
5.3	Test equipment, coupling fluid, test sensitivity and resolution of detection	6
5.3.1	Ultrasonic instrument	6
5.3.2	Probes and transducer frequencies	6
5.3.3	Checking of the ultrasonic test equipment	6
5.3.4	Coupling fluid	6
5.3.5	Test sensitivity and resolution of detection	7
5.4	Preparation of casting surfaces for testing	7
5.5	Test procedure	7
5.5.1	General	7
5.5.2	Range setting	8
5.5.3	Sensitivity setting	8
5.5.4	Consideration of various types of indications	9
5.5.5	Recording and recording limits	9
5.5.6	Assessment of indications to be recorded	9
5.5.7	Characterization and sizing of discontinuities	10
5.6	Test report	10
Annex A (normative) Resolution of detection of the instrument-probe combination		18
Annex B (informative) Sound-beam diameters		19
Annex C (informative) Types of indications generated by typical discontinuities		21
Bibliography		33