

# ISO 9556:2025-07 (E)

## Steel and iron - Determination of total carbon content - Infrared absorption method after combustion in an induction furnace

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Principle .....</b>	<b>1</b>
<b>5</b>	<b>Reagents .....</b>	<b>1</b>
<b>6</b>	<b>Apparatus .....</b>	<b>2</b>
<b>7</b>	<b>Sampling and sample preparation .....</b>	<b>3</b>
<b>8</b>	<b>Procedure .....</b>	<b>3</b>
<b>8.1</b>	<b>General operating instructions .....</b>	<b>3</b>
<b>8.2</b>	<b>Test portion .....</b>	<b>3</b>
<b>8.3</b>	<b>Blank test .....</b>	<b>4</b>
<b>8.4</b>	<b>Determination .....</b>	<b>4</b>
<b>8.5</b>	<b>Establishment of the calibration curve .....</b>	<b>4</b>
<b>8.5.1</b>	<b>Samples having carbon contents between 0,003 % (mass fraction) and 0,01 % (mass fraction) .....</b>	<b>4</b>
<b>8.5.2</b>	<b>Samples having carbon contents between 0,01 % (mass fraction) and 0,1 % (mass fraction) .....</b>	<b>5</b>
<b>8.5.3</b>	<b>Samples having carbon contents between 0,1 % (mass fraction) and 1,0 % (mass fraction) .....</b>	<b>6</b>
<b>8.5.4</b>	<b>Samples having carbon contents between 1,0 % (mass fraction) and 4,5 % (mass fraction) .....</b>	<b>6</b>
<b>9</b>	<b>Expression of results .....</b>	<b>7</b>
<b>9.1</b>	<b>Method of calculation .....</b>	<b>7</b>
<b>9.2</b>	<b>Precision .....</b>	<b>7</b>
<b>10</b>	<b>Test report .....</b>	<b>8</b>
<b>Annex A (informative) Additional information on the international precision tests .....</b>		<b>9</b>
<b>Annex B (informative) Graphical representation of precision data .....</b>		<b>11</b>
<b>Annex C (informative) Features of commercial high-frequency induction furnaces and infrared carbon analysers .....</b>		<b>12</b>
<b>Bibliography .....</b>		<b>14</b>