

ISO 4992-2:2006-02 (E)

Steel castings - Ultrasonic examination - Part 2: Steel castings for highly stressed components

| Contents | | Page |
|---|---|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Requirements | 2 |
| 4.1 | Order information | 2 |
| 4.2 | Extent of examination | 3 |
| 4.3 | Maximum permissible size of discontinuities | 3 |
| 4.4 | Personnel qualification | 3 |
| 4.5 | Wall-section zones | 4 |
| 4.6 | Severity levels | 4 |
| 5 | Examination | 4 |
| 5.1 | Principles | 4 |
| 5.2 | Material | 4 |
| 5.3 | Equipment, coupling medium, sensitivity and resolution of detection | 5 |
| 5.4 | Preparation of casting surfaces for testing | 6 |
| 5.5 | Examination procedure | 6 |
| 5.6 | Examination report | 9 |
| Annex A (normative) Resolution of detection of the instrument/probe combination | | 16 |
| Annex B (informative) Sound-beam diameters | | 17 |
| Annex C (informative) Types of indications | | 19 |
| Bibliography | | 31 |