

DIN EN 14399-8:2019-06 (E)

High-strength structural bolting assemblies for preloading - Part 8: System HV - Hexagon fit bolt and nut assemblies

Contents		Page
European foreword		3
Introduction		4
1	Scope	6
2	Normative references	6
3	Fit bolts	7
3.1	Dimensions of fit bolts	7
3.2	Specifications for fit bolts and reference standards	10
3.3	Marking of fit bolts	11
4	Nuts	11
4.1	Dimensions of nuts	11
4.2	Specification for nuts and reference standards	13
4.3	Decarburization of the nut thread	13
4.4	Marking of nuts	13
5	Designation of the bolt/nut assemblies	14
6	Associated washers	14
7	Functional characteristics of the bolt/nut/washers assembly	14
7.1	General	14
7.2	Maximum individual value of the bolt force during fitness for purpose test (Fbi max)	15
7.3	Values of angle 1	15
7.4	Values of angle 2	15
7.5	Individual values of the k-factor (ki), mean value of the k-factor (km) and coefficient of variation of the k-factor (Vk)	15
7.5.1	Individual values of the k-factor (ki) for k-class K1	15
7.5.2	Mean value of the k-factor (km) and coefficient of variation of the k-factor (Vk) for k-class K2	16
Annex A (normative) Clamp lengths and grip lengths		17
Bibliography		20