

DIN EN 14399-7:2008-03 (E)

High-strength structural bolting assemblies for preloading - Part 7: System HR - Countersunk head bolt and nut assemblies

Contents		Page
Foreword		3
Introduction		4
1 Scope		5
2 Normative references		5
3 Terms and definitions		6
4 Bolts		6
5 Nuts		12
6 Designation of the countersunk head bolt/nut assembly		16
7 Associated washers		16
8 Functional characteristics of the bolt/nut/washer(s) assembly		17
Bibliography		21
Figures Figure 1 -- Dimensions of bolts Table 2 -- Dimensions of bolts a		7
Figure 2 -- Example for marking of a bolt		12
Figure 3 -- Dimensions of nuts		12
Figure 4 -- Example for marking of a nut		16
Figure 5 -- Adapter		17
Figure 6 -- Test set-up		18
Tables Table 1 -- Systems of bolt/nut/washer(s) assemblies		4
Table 2 -- Dimensions of boltsa		8
Table 3 -- Specifications for bolts and reference standards		11
Table 4 -- Dimensions of nuts a		13
Table 5 -- Specifications for nuts and reference standards		14
Table 6 -- Proof load values of nuts		15
Table 7 -- Hardness values of nuts, if specified		15
Table 8 -- Characteristics of adapters		17
Table 9 -- Values for 1		19
Table 10 -- Values for 2		19