

# DIN EN 14399-7:2008-03 (E)

## High-strength structural bolting assemblies for preloading - Part 7: System HR - Countersunk head bolt and nut assemblies

---

| <b>Contents</b>  | <b>Page</b> |
|--|-------------|
| Foreword .....   | 3           |
| Introduction .....   | 4           |
| 1 Scope .....  | 5           |
| 2 Normative references .....   | 5           |
| 3 Terms and definitions .....  | 6           |
| 4 Bolts .....  | 6           |
| 5 Nuts .....   | 12          |
| 6 Designation of the countersunk head bolt/nut assembly .....                  | 16          |
| 7 Associated washers .....   | 16          |
| 8 Functional characteristics of the bolt/nut/washer(s) assembly .....          | 17          |
| Bibliography .....   | 21          |
| Figures Figure 1 -- Dimensions of bolts Table 2 -- Dimensions of bolts a ..... | 7           |
| Figure 2 -- Example for marking of a bolt .....                                | 12          |
| Figure 3 -- Dimensions of nuts .....   | 12          |
| Figure 4 -- Example for marking of a nut .....                                 | 16          |
| Figure 5 -- Adapter .....  | 17          |
| Figure 6 -- Test set-up .....  | 18          |
| Tables Table 1 -- Systems of bolt/nut/washer(s) assemblies .....               | 4           |
| Table 2 -- Dimensions of boltsa .....  | 8           |
| Table 3 -- Specifications for bolts and reference standards .....              | 11          |
| Table 4 -- Dimensions of nuts a .....  | 13          |
| Table 5 -- Specifications for nuts and reference standards .....               | 14          |
| Table 6 -- Proof load values of nuts .....                                     | 15          |
| Table 7 -- Hardness values of nuts, if specified .....                         | 15          |
| Table 8 -- Characteristics of adapters .....                                   | 17          |
| Table 9 -- Values for 1 .....  | 19          |
| Table 10 -- Values for 2 .....   | 19          |