DIN 267-27:2009-09 (E)

Fasteners - Part 27: Steel screws, bolts and studs with adhesive coating - Technical delivery conditions

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 5

4 Dimensions and designation 6
4.1 Standard coating 6
4.2 Non-standard coating 6
4.3 Designation 7

5 Requirements 8
5.1 General 8
5.1.1 Suitability test 8
5.1.2 System performance test 8
5.2 Test tightening torques, test torque ratios and test torques 8
5.2.1 Testing with preload 8
5.2.2 Testing without preload at ambient temperature ((23 ± 5) °C) and at temperatures of 100 °C and 150 °C 10
5.3 Coefficient of thread friction 10
5.4 Corrosion resistance 10
5.5 Long-term thermal stability 11

6 Testing 11
6.1 General 11
6.2 Determining breakaway torques, loosening torques and torque ratios 11
6.2.1 Testing with preload 11
6.2.2 Testing without preload 12
6.3 Determining the coefficient of thread friction 12
6.4 Testing for corrosion resistance 13
6.5 Testing for long-term thermal stability 13
6.6 Test equipment 13
6.6.1 Test bolt 13
6.6.2 Test nut 13
6.6.3 Test washer 14
6.6.4 Torque meter 14
6.6.5 Test assembly for determining the coefficient of friction 14
6.6.6 Oven for thermal stability testing 14

7 Miscellaneous functions 14
7.1 Sealing function 14
7.2 Bolting 14
7.2.1 Nut thread 14
7.2.2 Bolting procedure 15
7.3 Disassembly 15
7.4 Re-use of bolts 15

8 Condition on delivery 15

9 Storage 15

Annex A (informative) Explanatory notes regarding the system performance test 16

A.1 General 16
A.2 Verifying the suitability of microencapsulated coatings on surfaces with incorporated and/or additionally applied lubricants with regard to temperature effects 16

Bibliography 18