

DIN 267-27:2009-09 (E)

Fasteners - Part 27: Steel screws, bolts and studs with adhesive coating - Technical delivery conditions

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	5
4	Dimensions and designation	6
4.1	Standard coating	6
4.2	Non-standard coating	6
4.3	Designation	7
5	Requirements	8
5.1	General	8
5.1.1	Suitability test	8
5.1.2	System performance test	8
5.2	Test tightening torques, test torque ratios and test torques	8
5.2.1	Testing with preload	8
5.2.2	Testing without preload at ambient temperature (23 ± 5 °C) and at temperatures of 100 °C and 150 °C	10
5.3	Coefficient of thread friction	10
5.4	Corrosion resistance	10
5.5	Long-term thermal stability	11
6	Testing	11
6.1	General	11
6.2	Determining breakaway torques, loosening torques and torque ratios	11
6.2.1	Testing with preload	11
6.2.2	Testing without preload	12
6.3	Determining the coefficient of thread friction	12
6.4	Testing for corrosion resistance	13
6.5	Testing for long-term thermal stability	13
6.6	Test equipment	13
6.6.1	Test bolt	13
6.6.2	Test nut	13
6.6.3	Test washer	14
6.6.4	Torque meter	14
6.6.5	Test assembly for determining the coefficient of friction	14
6.6.6	Oven for thermal stability testing	14
7	Miscellaneous functions	14
7.1	Sealing function	14
7.2	Bolting	14
7.2.1	Nut thread	14
7.2.2	Bolting procedure	15
7.3	Disassembly	15
7.4	Re-use of bolts	15
8	Condition on delivery	15

9	Storage	15
	Annex A (informative) Explanatory notes regarding the system performance test	16
A.1	General	16
A.2	Verifying the suitability of microencapsulated coatings on surfaces with incorporated and/or additionally applied lubricants with regard to temperature effects	16
	Bibliography	18