

DIN 267-27:2009-09 (E)

Fasteners - Part 27: Steel screws, bolts and studs with adhesive coating - Technical delivery conditions

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 5 |
| 4 | Dimensions and designation | 6 |
| 4.1 | Standard coating | 6 |
| 4.2 | Non-standard coating | 6 |
| 4.3 | Designation | 7 |
| 5 | Requirements | 8 |
| 5.1 | General | 8 |
| 5.1.1 | Suitability test | 8 |
| 5.1.2 | System performance test | 8 |
| 5.2 | Test tightening torques, test torque ratios and test torques | 8 |
| 5.2.1 | Testing with preload | 8 |
| 5.2.2 | Testing without preload at ambient temperature (23 ± 5 °C) and at temperatures of 100 °C and 150 °C | 10 |
| 5.3 | Coefficient of thread friction | 10 |
| 5.4 | Corrosion resistance | 10 |
| 5.5 | Long-term thermal stability | 11 |
| 6 | Testing | 11 |
| 6.1 | General | 11 |
| 6.2 | Determining breakaway torques, loosening torques and torque ratios | 11 |
| 6.2.1 | Testing with preload | 11 |
| 6.2.2 | Testing without preload | 12 |
| 6.3 | Determining the coefficient of thread friction | 12 |
| 6.4 | Testing for corrosion resistance | 13 |
| 6.5 | Testing for long-term thermal stability | 13 |
| 6.6 | Test equipment | 13 |
| 6.6.1 | Test bolt | 13 |
| 6.6.2 | Test nut | 13 |
| 6.6.3 | Test washer | 14 |
| 6.6.4 | Torque meter | 14 |
| 6.6.5 | Test assembly for determining the coefficient of friction | 14 |
| 6.6.6 | Oven for thermal stability testing | 14 |
| 7 | Miscellaneous functions | 14 |
| 7.1 | Sealing function | 14 |
| 7.2 | Bolting | 14 |
| 7.2.1 | Nut thread | 14 |
| 7.2.2 | Bolting procedure | 15 |
| 7.3 | Disassembly | 15 |
| 7.4 | Re-use of bolts | 15 |
| 8 | Condition on delivery | 15 |

| | | |
|------------|--|-----------|
| 9 | Storage | 15 |
| | Annex A (informative) Explanatory notes regarding the system performance test | 16 |
| A.1 | General | 16 |
| A.2 | Verifying the suitability of microencapsulated coatings on surfaces with incorporated and/or additionally applied lubricants with regard to temperature effects | 16 |
| | Bibliography | 18 |