DIN EN ISO 10684:2011-09 (E)

Fasteners - Hot dip galvanized coatings (ISO 10684:2004 + Cor. 1:2008)

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 5

4 Materials 6
4.1 Raw material of parts 6
4.2 Zinc 6

5 Hot dip galvanizing procedures and precautions 6
5.1 Stress relief 6
5.2 Cleaning and pickling 6
5.3 Baking 6
5.4 Fluxing 6
5.5 Hot dip galvanizing 6
5.6 Spinning and quenching 7
5.7 Special requirements for nuts 7
5.8 Post-treatment 7

6 Requirements on thread tolerances and additional marking 7
6.1 General 7
6.2 Requirements and precautions in assembling hot dip galvanized threaded fasteners 7
6.3 Special requirements for marking when supplying fasteners in sealed containers 11

7 Mechanical properties of nuts tapped oversize and undersize threaded bolts, screws and studs 11

8 Coating requirements 11
8.1 Appearance of zinc coating 11
8.2 Considerations for hot dip galvanized washers 11
8.3 Zinc coating thickness 11
8.4 Adhesion of zinc coating 11

9 Lubrication 12

10 Ordering requirements 12

11 Designation 12

Annex A (normative) Special requirements for bolts, screws and nuts with thread sizes M8 and M10 14

Annex B (normative) Limits of sizes for hot dip galvanized internal and external screw thread M8 ... 16

Annex C (informative) Calculation of minimum ultimate tensile loads and proof loads for bolts and screws M8 and M10 with threads undersized to tolerance class 6az 18

Annex D (informative) Surface areas of bolts, screws and nuts 19

Annex E (normative) Adherence of hot-dip galvanized coating 22

Annex F (informative) Strength of hot dip galvanized bolt or screw and nut assemblies 23