

DIN EN 14399-3:2015-04 (E)

High-strength structural bolting assemblies for preloading - Part 3: System HR - Hexagon bolt and nut assemblies

Contents	Page
Foreword.....	3
Introduction	4
1 Scope	6
2 Normative references	6
3 Bolts	7
3.1 Dimensions of bolts.....	7
3.2 Specification for bolts and reference standard	11
3.3 Marking of bolts	11
4 Nuts	12
4.1 Dimensions of nuts.....	12
4.2 Specification for nuts and reference standards	14
4.3 Proof load values of nuts.....	15
4.4 Decarburization of the nut thread	15
4.5 Marking of nuts	15
5 Designation of the bolt/nut assemblies.....	16
6 Associated washers	16
7 Functional characteristics of the bolt/nut/washer(s) assembly.....	16
7.1 General.....	16
7.2 Maximum individual value of the bolt force during fitness for purpose test ($F_{bi,max}$)	17
7.3 Values of angle $\Delta\theta_1$	17
7.4 Values of angle $\Delta\theta_2$	17
7.5 Individual values of the k -factor (k_i), mean value of the k -factor (k_m) and coefficient of variation of the k -factor (V_k)	17
7.5.1 Individual values of the k -factor (k_i) for k -class K1.....	17
7.5.2 Mean value of the k -factor (k_m) and coefficient of variation of the k -factor (V_k) for k -class K2	18
Annex A (normative) Clamp lengths and grip lengths	19
A.1 Clamp lengths for bolting assemblies with one or two washers.....	19
A.2 Grip lengths for bolting assemblies with one or two washers	22
Bibliography	28