

DIN EN 14399-7:2019-06 (E)

High-strength structural bolting assemblies for preloading - Part 7: System HR - Countersunk head bolt and nut assemblies

| Contents | | Page |
|---|---|-------------|
| European foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Bolts | 7 |
| 3.1 | Dimensions of bolts | 7 |
| 3.2 | Specification for bolts and reference standard | 11 |
| 3.3 | Marking of bolts | 11 |
| 4 | Nuts | 12 |
| 4.1 | Dimensions of nuts | 12 |
| 4.2 | Specification for nuts and reference standards | 14 |
| 4.3 | Proof load values of nuts | 15 |
| 4.4 | Decarburisation of the nut thread | 15 |
| 4.5 | Marking of nuts | 16 |
| 5 | Designation of the bolt/nut assemblies | 16 |
| 6 | Associated washers | 16 |
| 7 | Functional characteristics of the bolt/nut/washer assembly | 17 |
| 7.1 | General | 17 |
| 7.2 | Maximum individual value of the bolt force during fitness for purpose test (F_{bi max}) | 18 |
| 7.3 | Values of angle 1 | 18 |
| 7.4 | Values of angle 2 | 19 |
| 7.5 | Individual values of the k-factor (k_i), mean value of the k-factor (k_m) and coefficient of variation of the k-factor (V_k) | 19 |
| 7.5.1 | Individual values of the k-factor (k_i) for k-class K1 | 19 |
| 7.5.2 | Mean value of the k-factor (k_m) and coefficient of variation of the k-factor (V_k) for k-class K2 | 19 |
| Annex A (normative) Clamp lengths and grip lengths | | 21 |
| A.1 | Clamp lengths for countersunk head bolting assemblies | 21 |
| A.2 | Grip lengths for countersunk head bolting assemblies | 24 |
| Bibliography | | 27 |