

DIN EN 14399-7:2019-06 (E)

High-strength structural bolting assemblies for preloading - Part 7: System HR - Countersunk head bolt and nut assemblies

Contents		Page
European foreword		3
Introduction		4
1	Scope	6
2	Normative references	6
3	Bolts	7
3.1	Dimensions of bolts	7
3.2	Specification for bolts and reference standard	11
3.3	Marking of bolts	11
4	Nuts	12
4.1	Dimensions of nuts	12
4.2	Specification for nuts and reference standards	14
4.3	Proof load values of nuts	15
4.4	Decarburisation of the nut thread	15
4.5	Marking of nuts	16
5	Designation of the bolt/nut assemblies	16
6	Associated washers	16
7	Functional characteristics of the bolt/nut/washer assembly	17
7.1	General	17
7.2	Maximum individual value of the bolt force during fitness for purpose test (F_{bi max})	18
7.3	Values of angle 1	18
7.4	Values of angle 2	19
7.5	Individual values of the k-factor (k_i), mean value of the k-factor (k_m) and coefficient of variation of the k-factor (V_k)	19
7.5.1	Individual values of the k-factor (k_i) for k-class K1	19
7.5.2	Mean value of the k-factor (k_m) and coefficient of variation of the k-factor (V_k) for k- class K2	19
Annex A (normative) Clamp lengths and grip lengths		21
A.1	Clamp lengths for countersunk head bolting assemblies	21
A.2	Grip lengths for countersunk head bolting assemblies	24
Bibliography		27