

DIN EN 14399-9:2019-06 (E)

High-strength structural bolting assemblies for preloading - Part 9: System HR or HV - Direct tension indicators for bolt and nut assemblies

| Contents | | Page |
|---|---|-------------|
| European foreword | | 3 |
| Introduction | | 5 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Direct tension indicators | 8 |
| 3.1 | General | 8 |
| 3.2 | Dimensions | 8 |
| 3.3 | Specifications and reference standards for direct tension indicators | 10 |
| 3.4 | Functional test of direct tension indicators | 11 |
| 3.5 | Test method for measuring compression loads (all finishes) on direct tension indicators | 12 |
| 3.5.1 | General | 12 |
| 3.5.2 | Testing apparatus | 12 |
| 3.5.3 | Support blocks | 13 |
| 3.5.4 | Bearing blocks | 14 |
| 3.5.5 | Calibration | 14 |
| 3.5.6 | Test procedure | 14 |
| 3.6 | Marking of the direct tension indicator | 17 |
| 3.7 | Designation of the direct tension indicator | 17 |
| 4 | Nut face washers (HN) and bolt face washers (HB) | 17 |
| 4.1 | Dimensions | 17 |
| 4.2 | Specifications and reference standards for nut face washers (HN) and bolt face washers (HB) | 19 |
| 4.3 | Marking | 20 |
| 4.3.1 | Nut face washers (HN) | 20 |
| 4.3.2 | Bolt face washers (HB) | 20 |
| 4.4 | Designation of nut face washers (HN) and bolt face washers (HB) | 21 |
| 5 | Functional characteristics | 21 |
| 5.1 | Bolting assemblies | 21 |
| 5.2 | Functional characteristics of direct tension indicators in the assembly | 22 |
| 5.3 | Functional characteristics of bolting assemblies with direct tension indicator | 23 |
| 5.3.1 | General | 23 |
| 5.3.2 | Suitability test procedures | 23 |
| Annex A (informative) Use of structural bolting assemblies for preloading with direct tension indicators | | 25 |
| A.1 | General | 25 |
| A.2 | Bolting assembly configurations | 25 |
| A.3 | Checking | 26 |
| Bibliography | | 29 |