

# DIN 267-27:2024-07 (E)

## Fasteners - Part 27: Steel screws, bolts and studs made of steel with pre-adhesive coating - Technical specifications

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
1	Scope .....	6
2	Normative references .....	6
3	Terms and definitions .....	7
4	Dimensions and designation .....	9
4.1	Coating as a rule .....	9
4.2	Coatings with special length and/or position .....	9
4.3	Designation .....	10
4.3.1	General .....	10
4.3.2	Designation example for a coating as a rule .....	10
4.3.3	Examples of designations for coatings with a special length and/or position .....	11
5	Requirements .....	11
5.1	General .....	11
5.1.1	Suitability test .....	11
5.1.2	System test .....	11
5.2	Test torques, test tightening torques and test torque ratios .....	13
5.2.1	Testing without preload at room temperature (23 ± 5) °C, 100 °C and 150 °C .....	13
5.2.2	Testing with preload .....	14
5.3	Thread friction coefficients .....	15
5.4	Resistance to aggressive media .....	15
5.5	Resistance to long-term effects at elevated temperatures .....	15
6	Test procedure .....	15
6.1	General .....	15
6.2	Test of breakaway torques, prevailing-off torques and test torque ratios .....	15
6.2.1	Testing without preload .....	15
6.2.2	Testing with preload .....	16
6.3	Testing of thread friction coefficients .....	18
6.4	Testing the resistance to aggressive media .....	18
6.5	Testing the resistance to long-term effects of elevated temperatures .....	19
6.6	Test specimens and test devices .....	19
6.6.1	Test bolt .....	19
6.6.2	Test nut .....	19
6.6.3	Test washer .....	19
6.6.4	Torque measuring device .....	19
6.6.5	Test device for evaluation of thread friction coefficients .....	19
6.6.6	Oven for testing temperature resistance .....	20
7	Auxiliary functions and application notes .....	20
7.1	Sealing function .....	20
7.2	Fastening in practice .....	20
7.2.1	Nut thread .....	20
7.2.2	Fastening process .....	20
7.3	Loosening capability .....	20
7.4	Reuse .....	20
7.5	Design information .....	21

8	Delivery .....	21
9	Shelf life .....	21
<b>Annex A (informative) Influence of the engaged adhesive length on the locking effect of MK coatings .....</b>		<b>23</b>
<b>Annex B (informative) Explanations on the locking effect of MK coatings on bolts with surfaces with integral and/or additionally applied lubricants (testing with preload) .....</b>		<b>24</b>
<b>Bibliography .....</b>		<b>26</b>
<b>Figures Figure 1 -- Examples for length and position of the coating as a rule .....</b>		<b>9</b>
<b>Figure 2 -- Examples of coatings of a particular length and position .....</b>		<b>10</b>
<b>Figure 3 -- Test procedure for testing without preload .....</b>		<b>16</b>
<b>Figure 4 -- Test arrangement with test strip .....</b>		<b>17</b>
<b>Figure 5 -- Test arrangement with test sleeve .....</b>		<b>17</b>
<b>Figure 6 -- Test procedure for testing with preload .....</b>		<b>18</b>
<b>Figure B.1 -- Loosening torque ratio ML/MA of bolts without adhesive protection (unsecured bolts) as a function of the coefficient of friction <math>\mu_{ges}</math> (here for example for M6 bolts); assumptions: Bearing geometry according to DIN EN ISO 4014, preload loss due to setting 10 % .....</b>		<b>24</b>
<b>Tables Table 1 -- Test torques at room temperature, 100 °C and 150 °C (without preload) .....</b>		<b>13</b>
<b>Table 2 -- Test torques and test torque ratios at room temperature, 100 °C and 150 °C (with preload) .....</b>		<b>14</b>