DIN 267-27:2024-07 (E)

Fasteners - Part 27: Steel screws, bolts and studs made of steel with pre-adhesive coating - Technical specifications

Contents

Page

Foreword 4

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Dimensions and designation 9
4.1 Coating as a rule 9
4.2 Coatings with special length and/or position 9
4.3 Designation 10
4.3.1 General 10
4.3.2 Designation example for a coating as a rule 10
4.3.3 Examples of designations for coatings with a special length and/or position 11

5 Requirements 11
5.1 General 11
5.1.1 Suitability test 11
5.1.2 System test 11
5.2 Test torques, test tightening torques and test torque ratios 13
5.2.1 Testing without preload at room temperature (23 ± 5) °C, 100 °C and 150 °C 13
5.2.2 Testing with preload 14
5.3 Thread friction coefficients 15
5.4 Resistance to aggressive media 15
5.5 Resistance to long-term effects at elevated temperatures 15

6 Test procedure 15
6.1 General 15
6.2 Test of breakaway torques, prevailing-off torques and test torque ratios 15
6.2.1 Testing without preload 15
6.2.2 Testing with preload 16
6.3 Testing of thread friction coefficients 18
6.4 Testing the resistance to aggressive media 18
6.5 Testing the resistance to long-term effects of elevated temperatures 19
6.6 Test specimens and test devices 19
6.6.1 Test bolt 19
6.6.2 Test nut 19
6.6.3 Test washer 19
6.6.4 Torque measuring device 19
6.6.5 Test device for evaluation of thread friction coefficients 19
6.6.6 Oven for testing temperature resistance 20

7 Auxiliary functions and application notes 20
7.1 Sealing function 20
7.2 Fastening in practice 20
7.2.1 Nut thread 20
7.2.2 Fastening process 20
7.3 Loosening capability 20
7.4 Reuse 20
7.5 Design information 21

8 Delivery 21

9 Shelf life 21

Annex A (informative) Influence of the engaged adhesive length on the locking effect of MK coatings 23

Annex B (informative) Explanations on the locking effect of MK coatings on bolts with surfaces with integral and/or additionally applied lubricants (testing with preload) 24

Bibliography 26

Figures Figure 1 -- Examples for length and position of the coating as a rule 9

Figure 2 -- Examples of coatings of a particular length and position 10

Figure 3 -- Test procedure for testing without preload 16

Figure 4 -- Test arrangement with test strip 17

Figure 5 -- Test arrangement with test sleeve 17

Figure 6 -- Test procedure for testing with preload 18

Figure B.1 -- Loosening torque ratio ML/MA of bolts without adhesive protection (unsecured bolts) as a function of the coefficient of friction µges (here for example for M6 bolts); assumptions: Bearing geometry according to DIN EN ISO 4014, preload loss due to setting 10 % 24

Tables Table 1 -- Test torques at room temperature, 100 °C and 150 °C (without preload) 13

Table 2 -- Test torques and test torque ratios at room temperature, 100 °C and 150 °C (with preload) 14