

# DIN EN ISO 10642:2026-06 (E)

## Fasteners - Hexagon socket countersunk head screws with reduced loadability (ISO 10642:2026)

---

| <b>Contents</b>  |  | <b>Page</b> |
|--|--|-------------|
| Foreword.....  |  | iv          |
| <b>1</b> <b>Scope</b> .....  |  | <b>1</b>    |
| <b>2</b> <b>Normative references</b> .....   |  | <b>1</b>    |
| <b>3</b> <b>Terms and definitions</b> .....  |  | <b>2</b>    |
| <b>4</b> <b>Dimensions and gauging of head</b> .....   |  | <b>2</b>    |
| 4.1    Dimensions.....   |  | 2           |
| 4.1.1    Gauging of head.....  |  | 6           |
| <b>5</b> <b>Requirements and reference International Standards</b> .....   |  | <b>6</b>    |
| <b>6</b> <b>Marking and labelling</b> .....  |  | <b>8</b>    |
| 6.1    Marking on product.....   |  | 8           |
| 6.2    Labelling on package.....   |  | 8           |
| <b>7</b> <b>Designation</b> .....  |  | <b>9</b>    |
| <b>Annex A (informative) Minimum ultimate tensile loads for bolts and screws with full loadability, coarse pitch threads M2 and M2,5</b> ..... |  | <b>10</b>   |
| <b>Bibliography</b> .....  |  | <b>11</b>   |