ISO 10684:2004-07 (E)

Fasteners - Hot dip galvanized coatings

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Materials 3
4.1 Raw material of parts 3
4.2 Zinc 3

5 Hot dip galvanizing procedures and precautions 3
5.1 Stress relief 3
5.2 Cleaning and pickling 3
5.3 Baking 3
5.4 Fluxing 3
5.5 Hot dip galvanizing 3
5.6 Spinning and quenching 4
5.7 Special requirements for nuts 4
5.8 Post-treatment 4

6 Requirements on thread tolerances and additional marking 4
6.1 General 4
6.2 Requirements and precautions in assembling hot dip galvanized threaded fasteners 4
6.3 Special requirements for marking when supplying fasteners in sealed containers 8

7 Mechanical properties of nuts tapped oversize and undersize threaded bolts, screws and studs 8

8 Coating requirements 8
8.1 Appearance of zinc coating 8
8.2 Considerations for hot dip galvanized washers 8
8.3 Zinc coating thickness 8
8.4 Adhesion of zinc coating 8

9 Lubrication 9

10 Ordering requirements 9

11 Designation 9

Annex A (normative) Special requirements for bolts, screws and nuts with thread sizes M8 and M10 11

Annex B (normative) Limits of sizes for hot dip galvanized internal and external screw thread M8 ... 13

Annex C (informative) Calculation of minimum ultimate tensile loads and proof loads for bolts and screws M8 and M10 with threads undersized to tolerance class 6az 15

Annex D (informative) Surface areas of bolts, screws and nuts 16

Annex E (normative) Adherence of hot-dip galvanized coating 19

Annex F (informative) Strength of hot dip galvanized bolt or screw and nut assemblies 20