

ISO 10684:2004-07 (E)

Fasteners - Hot dip galvanized coatings

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Materials	3
4.1	Raw material of parts	3
4.2	Zinc	3
5	Hot dip galvanizing procedures and precautions	3
5.1	Stress relief	3
5.2	Cleaning and pickling	3
5.3	Baking	3
5.4	Fluxing	3
5.5	Hot dip galvanizing	3
5.6	Spinning and quenching	4
5.7	Special requirements for nuts	4
5.8	Post-treatment	4
6	Requirements on thread tolerances and additional marking	4
6.1	General	4
6.2	Requirements and precautions in assembling hot dip galvanized threaded fasteners	4
6.3	Special requirements for marking when supplying fasteners in sealed containers	8
7	Mechanical properties of nuts tapped oversize and undersize threaded bolts, screws and studs	8
8	Coating requirements	8
8.1	Appearance of zinc coating	8
8.2	Considerations for hot dip galvanized washers	8
8.3	Zinc coating thickness	8
8.4	Adhesion of zinc coating	8
9	Lubrication	9
10	Ordering requirements	9
11	Designation	9
Annex A (normative)	Special requirements for bolts, screws and nuts with thread sizes M8 and M10	11
Annex B (normative)	Limits of sizes for hot dip galvanized internal and external screw thread M8 ...	13
Annex C (informative)	Calculation of minimum ultimate tensile loads and proof loads for bolts and screws M8 and M10 with threads undersized to tolerance class 6az	15
Annex D (informative)	Surface areas of bolts, screws and nuts	16
Annex E (normative)	Adherence of hot-dip galvanized coating	19
Annex F (informative)	Strength of hot dip galvanized bolt or screw and nut assemblies	20