

# ISO 7240-8:2007-08 (E)

## Fire detection and alarm systems - Part 8: Carbon monoxide fire detectors using an electro-chemical cell in combination with a heat sensor

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vii
1	Scope .....	1
2	Normative references .....	1
3	Definitions .....	2
4	General requirements .....	2
4.1	Compliance .....	2
4.2	Individual alarm indication .....	2
4.3	Connection of ancillary devices .....	2
4.4	Monitoring of detachable detectors .....	2
4.5	Manufacturer's adjustments .....	2
4.6	On-site adjustment of response behaviour .....	2
4.7	Rate-sensitive response behaviour .....	3
4.8	Marking .....	3
4.9	Data .....	4
4.10	Requirements for software controlled detectors .....	4
5	Tests .....	5
5.1	General .....	5
5.2	Repeatability of CO response .....	8
5.3	Directional dependence of CO response .....	8
5.4	Directional dependence of heat response .....	8
5.5	Lower limit of heat sensitivity .....	10
5.6	Reproducibility of CO response .....	10
5.7	Reproducibility of heat response .....	11
5.8	Exposure to chemical agents at environmental concentrations .....	11
5.9	Long-term stability of CO response .....	12
5.10	Saturation .....	12
5.11	Exposure to chemical agents that can be present during a fire .....	13
5.12	Variation in supply parameters .....	14
5.13	Air movement .....	15
5.14	Dry heat (operational) .....	15
5.15	Cold (operational) .....	16
5.16	Damp heat, cyclic (operational) .....	17
5.17	Damp heat, steady state (endurance) .....	18
5.18	Low humidity, steady state (endurance) .....	19
5.19	Sulfur dioxide (SO <sub>2</sub> ) corrosion (endurance) .....	20
5.20	Shock (operational) .....	21
5.21	Impact (operational) .....	22
5.22	Vibration, sinusoidal (operational) .....	23
5.23	Vibration, sinusoidal (endurance) .....	24
5.24	Electromagnetic compatibility (EMC), immunity tests (operational) .....	25
5.25	Fire sensitivity .....	26
6	Test report .....	28

<b>Annex A (normative) Gas test chamber for response threshold value and cross sensitivity measurements .....</b>	<b>29</b>
<b>Annex B (normative) Heat tunnel for response time and response temperature measurements .....</b>	<b>30</b>
<b>Annex C (normative) Apparatus for impact test .....</b>	<b>31</b>
<b>Annex D (normative) Fire test room .....</b>	<b>33</b>
<b>Annex E (normative) Smouldering (pyrolysis) wood fire (TF2) .....</b>	<b>35</b>
<b>Annex F (normative) Glowing smouldering cotton fire (TF3) .....</b>	<b>38</b>
<b>Annex G (normative) Open plastics (polyurethane) fire (TF4) .....</b>	<b>41</b>
<b>Annex H (normative) Liquid (heptane) fire (TF5) .....</b>	<b>43</b>
<b>Annex I (normative) Deep-seated smouldering cotton fire (TF9) .....</b>	<b>45</b>
<b>Annex J (informative) Information concerning the construction of the gas test chamber .....</b>	<b>47</b>
<b>Annex K (informative) Construction of the heat tunnel .....</b>	<b>49</b>