

# ISO 7240-17:2009-08 (E)

## Fire detection and fire alarm systems - Part 17: Short-circuit isolators

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Requirements .....</b>	<b>2</b>
<b>4.1</b>	<b>Compliance .....</b>	<b>2</b>
<b>4.2</b>	<b>Integral status indication .....</b>	<b>2</b>
<b>4.3</b>	<b>Connection of ancillary devices .....</b>	<b>2</b>
<b>4.4</b>	<b>Monitoring of detachable short-circuit isolators .....</b>	<b>3</b>
<b>4.5</b>	<b>Manufacturer's adjustments .....</b>	<b>3</b>
<b>4.6</b>	<b>On-site adjustments .....</b>	<b>3</b>
<b>4.7</b>	<b>Marking .....</b>	<b>3</b>
<b>4.8</b>	<b>Data .....</b>	<b>3</b>
<b>4.9</b>	<b>Additional requirements for software controlled short-circuit isolators .....</b>	<b>4</b>
<b>5</b>	<b>Tests .....</b>	<b>5</b>
<b>5.1</b>	<b>General .....</b>	<b>5</b>
<b>5.2</b>	<b>Reproducibility .....</b>	<b>7</b>
<b>5.3</b>	<b>Variation in supply voltage .....</b>	<b>8</b>
<b>5.4</b>	<b>Dry heat (operational) .....</b>	<b>8</b>
<b>5.5</b>	<b>Cold (operational) .....</b>	<b>9</b>
<b>5.6</b>	<b>Damp heat, cyclic (operational) .....</b>	<b>10</b>
<b>5.7</b>	<b>Damp heat, steady state (endurance) .....</b>	<b>10</b>
<b>5.8</b>	<b>Sulfur dioxide (SO<sub>2</sub>) corrosion (endurance) .....</b>	<b>11</b>
<b>5.9</b>	<b>Shock (operational) .....</b>	<b>12</b>
<b>5.10</b>	<b>Impact (operational) .....</b>	<b>13</b>
<b>5.11</b>	<b>Vibration, sinusoidal (operational) .....</b>	<b>14</b>
<b>5.12</b>	<b>Vibration, sinusoidal (endurance) .....</b>	<b>15</b>
<b>5.13</b>	<b>Electromagnetic compatibility (EMC), immunity tests (operational) .....</b>	<b>16</b>
<b>6</b>	<b>Test report .....</b>	<b>17</b>
<b>Annex A (informative) Examples for the functional test procedure .....</b>		<b>18</b>
<b>Annex B (informative) Apparatus for impact test .....</b>		<b>25</b>
<b>Bibliography .....</b>		<b>27</b>