

ISO 6182-12:2010-01 (E)

Fire protection - Automatic sprinkler systems - Part 12: Requirements and test methods for grooved-end components for steel pipe systems

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Product consistency	2
5	Product assembly	3
6	Requirements	3
6.1	Grooved-end dimensions	3
6.2	Minimum pipe wall thickness	3
6.3	Mechanical coupling housing	3
6.4	Pressure-responsive gasket	3
6.5	Bolts	3
6.6	Nuts	8
6.7	Hinge pins	8
6.8	Flexible coupling	8
6.9	Vacuum	8
6.10	Air leakage	8
6.11	Low-temperature exposure	8
6.12	Heat ageing	8
6.13	Hydrostatic pressure	8
6.14	Bending moment	8
6.15	Gasket material evaluation	8
6.16	Fire resistance	9
6.17	Rated working pressure	9
6.18	Nominal sizes	9
7	Test methods	9
7.1	Test assembly	9
7.2	Vacuum	9
7.3	Air leakage	10
7.4	Low-temperature exposure	10
7.5	Heat aging	11
7.6	Hydrostatic pressure test	11
7.7	Bending moment	11
7.8	Fire resistance	13
8	Markings	13
8.1	Housing markings	13
8.2	Gasket markings	14
8.3	Manufacturer's installation instructions	14
Bibliography		15