

# ISO 7240-6:2011-06 (E)

## Fire detection and alarm systems - Part 6: Carbon monoxide fire detectors using electro-chemical cells

---

| <b>Contents</b>     |  | <b>Page</b> |
|---------------------|--|-------------|
| Foreword .....      |  | v           |
| Introduction .....  |  | vii         |
| 1                   | Scope .....  | 1           |
| 2                   | Normative references .....   | 1           |
| 3                   | Terms and definitions .....  | 2           |
| 4                   | Requirements .....   | 2           |
| 4.1                 | Compliance .....   | 2           |
| 4.2                 | Individual alarm indication .....  | 2           |
| 4.3                 | Connection of ancillary devices .....  | 2           |
| 4.4                 | Monitoring of detachable detectors .....   | 2           |
| 4.5                 | Manufacturer's adjustments .....   | 2           |
| 4.6                 | On-site adjustment of response behaviour .....   | 3           |
| 4.7                 | Rate-sensitive response behaviour .....  | 3           |
| 4.8                 | Marking .....  | 3           |
| 4.9                 | Data .....   | 4           |
| 4.10                | Requirements for software controlled detectors .....                                   | 4           |
| 5                   | Test methods .....   | 5           |
| 5.1                 | General .....  | 5           |
| 5.2                 | Repeatability .....  | 8           |
| 5.3                 | Directional dependence .....   | 9           |
| 5.4                 | Reproducibility .....  | 9           |
| 5.5                 | Exposure to chemical agents at environmental concentrations .....                      | 10          |
| 5.6                 | Long-term stability .....  | 11          |
| 5.7                 | Saturation .....   | 11          |
| 5.8                 | Exposure to chemical agents that can be present during a fire .....                    | 12          |
| 5.9                 | Variation in supply parameters .....   | 13          |
| 5.10                | Air movement .....   | 13          |
| 5.11                | Dry heat (operational) .....   | 14          |
| 5.12                | Cold (operational) .....   | 15          |
| 5.13                | Damp heat cyclic (operational) .....   | 16          |
| 5.14                | Damp heat, steady state (endurance) .....  | 17          |
| 5.15                | Low humidity, steady state (endurance) .....   | 17          |
| 5.16                | Sulfur dioxide (SO <sub>2</sub> ) corrosion (endurance) .....                          | 18          |
| 5.17                | Shock (operational) .....  | 19          |
| 5.18                | Impact (operational) .....   | 20          |
| 5.19                | Vibration, sinusoidal (operational) .....  | 21          |
| 5.20                | Vibration, sinusoidal (endurance) .....  | 22          |
| 5.21                | Electromagnetic compatibility (EMC) immunity test (operational) .....                  | 23          |
| 5.22                | Fire sensitivity .....   | 23          |
| 6                   | Test report .....  | 25          |
| Annex A (normative) | Gas test chamber for response threshold value and cross-sensitivity measurements ..... | 26          |

|  |           |
|--|-----------|
| <b>Annex B (normative) Apparatus for impact test .....</b>   | <b>27</b> |
| <b>Annex C (normative) Fire test room .....</b>  | <b>29</b> |
| <b>Annex D (normative) Smouldering (pyrolysis) wood fire (TF2) .....</b>                           | <b>31</b> |
| <b>Annex E (normative) Glowing smouldering cotton fire (TF3) .....</b>                             | <b>34</b> |
| <b>Annex F (normative) Deep-seated smouldering cotton fire (TF9) .....</b>                         | <b>37</b> |
| <b>Annex G (informative) Information concerning the construction of the gas test chamber .....</b> | <b>40</b> |
| <b>Bibliography .....</b>  | <b>42</b> |