

ISO 7240-6:2011-06 (E)

Fire detection and alarm systems - Part 6: Carbon monoxide fire detectors using electro-chemical cells

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Requirements	2
4.1	Compliance	2
4.2	Individual alarm indication	2
4.3	Connection of ancillary devices	2
4.4	Monitoring of detachable detectors	2
4.5	Manufacturer's adjustments	2
4.6	On-site adjustment of response behaviour	3
4.7	Rate-sensitive response behaviour	3
4.8	Marking	3
4.9	Data	4
4.10	Requirements for software controlled detectors	4
5	Test methods	5
5.1	General	5
5.2	Repeatability	8
5.3	Directional dependence	9
5.4	Reproducibility	9
5.5	Exposure to chemical agents at environmental concentrations	10
5.6	Long-term stability	11
5.7	Saturation	11
5.8	Exposure to chemical agents that can be present during a fire	12
5.9	Variation in supply parameters	13
5.10	Air movement	13
5.11	Dry heat (operational)	14
5.12	Cold (operational)	15
5.13	Damp heat cyclic (operational)	16
5.14	Damp heat, steady state (endurance)	17
5.15	Low humidity, steady state (endurance)	17
5.16	Sulfur dioxide (SO ₂) corrosion (endurance)	18
5.17	Shock (operational)	19
5.18	Impact (operational)	20
5.19	Vibration, sinusoidal (operational)	21
5.20	Vibration, sinusoidal (endurance)	22
5.21	Electromagnetic compatibility (EMC) immunity test (operational)	23
5.22	Fire sensitivity	23
6	Test report	25
Annex A (normative)	Gas test chamber for response threshold value and cross-sensitivity measurements	26

Annex B (normative) Apparatus for impact test	27
Annex C (normative) Fire test room	29
Annex D (normative) Smouldering (pyrolysis) wood fire (TF2)	31
Annex E (normative) Glowing smouldering cotton fire (TF3)	34
Annex F (normative) Deep-seated smouldering cotton fire (TF9)	37
Annex G (informative) Information concerning the construction of the gas test chamber	40
Bibliography	42