

ISO 7076-2:2012-05 (E)

Fire protection - Foam fire extinguishing systems - Part 2: Low expansion foam equipment

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Requirements	3
4.1	Connections	3
4.2	Parts for removal during routine field maintenance	3
4.3	Corrosion resistance of metal parts	3
4.4	Elastomeric joint rings	3
4.5	Plastics and reinforced resin materials	3
4.6	Strength	4
4.7	Leak resistance	4
4.8	Discharge coefficient (K factor)	4
4.9	Foam quality	4
4.10	Water flow	5
4.11	Range of discharge	5
4.12	Vapour seal	5
4.13	Operation reliability	5
4.14	Stress corrosion	5
4.15	Salt-spray corrosion	5
4.16	Light and water exposure	5
4.17	Heat and fire resistance	6
5	Test methods	6
5.1	General	6
5.2	Ageing test for plastics and reinforced resin materials	6
5.3	Liquid exposure test	6
5.4	Equipment pressurization test	6
5.5	Leak resistance test	6
5.6	Flow coefficient measurement	6
5.7	Measurement of expansion ratio and drainage time	7
5.8	Water flow test	7
5.9	Range tests for branchpipe and monitor	7
5.10	Vapour sealing test	7
5.11	Operation reliability test	7
5.12	Stress corrosion test	8
5.13	Salt-spray corrosion test	8
5.14	Light and water exposure test	9
5.15	Heat and fire resistance	9
6	Marking	9
7	Manufacturer's installation and operation instructions	9
Annex A (normative)	Tolerances	10
Bibliography		11