

ISO 7240-10:2012-05 (E)

Fire detection and alarm systems - Part 10: Point-type flame detectors

Contents		Page
Foreword		iv
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Abbreviated terms	2
5	General requirements	3
5.1	Compliance	3
5.2	Classification	3
5.3	Individual alarm indication	3
5.4	Connection of ancillary devices	3
5.5	Monitoring of detachable detectors	3
5.6	Manufacturer adjustments	3
5.7	On-site sensitivity adjustment	4
5.8	Ingress protection (IP) -- Optional function	4
5.9	Marking	4
5.10	Data	5
5.11	Requirements for software-controlled detectors	5
6	Tests	6
6.1	General	6
6.2	Reproducibility	9
6.3	Repeatability	10
6.4	Directional dependence	10
6.5	Fire sensitivity	11
6.6	Dazzling (operational)	14
6.7	Dry heat (operational)	15
6.8	Cold (operational)	16
6.9	Damp heat, cyclic (operational)	16
6.10	Damp heat, steady state (endurance)	17
6.11	Sulfur dioxide (SO₂) corrosion (endurance)	18
6.12	Shock (operational)	19
6.13	Impact (operational)	20
6.14	Vibration, sinusoidal (operational)	21
6.15	Vibration, sinusoidal (endurance)	22
6.16	Variation of supply parameters (operational)	23
6.17	EMC immunity tests (operational)	23
6.18	IP -- Optional function	24
7	Test report	25
Annex A (normative) Apparatus for response point determination		26
Annex B (normative) Liquid (heptane) fire (TF5)		28
Annex C (normative) Liquid (methylated spirit) fire (TF6)		29

Annex D (normative) Apparatus for dazzling test	30
Annex E (normative) Apparatus for impact test	31
Annex F (informative) Example of methane burner	33