

ISO 6182-5:2012-12 (E)

Fire protection - Automatic sprinkler systems - Part 5: Requirements and test methods for deluge valves

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Requirements	4
4.1	Nominal sizes	4
4.2	Connections	4
4.3	Rated working pressure	4
4.4	Body and cover	4
4.5	Strength (see 6.8)	5
4.6	Access for maintenance	5
4.7	Components	5
4.8	Leakage (see 6.7)	6
4.9	Non-metallic components (excluding gaskets, diaphragms, seals and other elastomeric parts) (see 6.4 & 6.5)	6
4.10	Sealing assembly elements (see 6.3)	6
4.11	Clearances	6
4.12	Hydraulic friction loss (see 6.6)	8
4.13	Endurance (see 6.10)	9
4.14	Operational performance (see 6.9)	9
4.15	Drains	9
4.16	Alarms	10
4.17	Valve impairment	10
4.18	Height limitations of wet pilot lines	10
5	Production testing and quality control	11
6	Tests	11
6.1	Samples	11
6.2	Spring and diaphragm test	11
6.3	Sealing element tests (see 4.10)	11
6.4	Warm-water ageing test for non-metallic components (excluding gaskets and seals and other elastomeric parts) (see 4.9)	12
6.5	Air ageing test for non-metallic components (excluding gaskets and seals and other elastomeric parts) (see 4.9)	12
6.6	Hydraulic friction loss test (see 4.12)	13
6.7	Valve leakage and deformation test (see 4.8)	13
6.8	Body strength test (see 4.5)	13
6.9	Operational test (see 4.14)	13
6.10	Endurance test (see 4.13)	15
6.11	Anti-reseating test (see 4.7.7)	15
6.12	Salt mist corrosion test	15
7	Marking	16
8	Manufacturer's installation instructions	17

Annex A (normative) Tolerances	18
Bibliography	19