DIN EN 14044:2014-04 (E)

High rise aerial appliances for fire and rescue service use - Turntable l adders with sequential movements - Safety and performance requirements and test methods

Contents

Page

Foreword 4

Introduction 7

1 Scope 8

2 Normative references 8

3 Terms and definitions, symbols and abbreviated terms 9

4 List of significant hazards 20

5 Requirements 28
5.1 Safety requirements and/or measures 28
5.1.1 General 28
5.1.2 Requirements in respect of stability 29
5.1.3 Requirements relating to the strength of the turntable ladder 41
5.1.4 Verification of vehicle performance by functional testing 43
5.1.5 Requirements relating to function 44
5.1.6 Requirements relating to noise 71
5.2 Performance requirements 72
5.2.1 Operational requirements 72
5.2.2 Requirements demanded by national regulations 72
5.2.3 Overall maximum dimensions 73
5.2.4 Maximum gross laden mass 73
5.2.5 Radio interference 74

6 Designation 75

7 Information for use 75
7.1 General 75
7.2 Instruction handbook 75
7.2.1 General 75
7.2.2 Operating instruction 75
7.2.3 Transport, handling and storage information 77
7.2.4 Information on commissioning 77
7.2.5 Machine details 77
7.2.6 Maximum loads in the rescue cage and/or on the ladder set 78
7.2.7 Maintenance information for use by trained personnel 78
7.2.8 Special working methods or conditions 78
7.2.9 Periodical examinations and tests 78
7.3 Marking 79

Annex A (informative) **Example of table reporting the stability tests** 81

Annex B (normative) **Operating time** 82

Annex C (informative) **List of nominal reaches in several European countries applicable to turntable ladders** 83

Annex D (informative) **Verification and reception tests** 85

Annex ZA (informative) **Relationship between this European Standard and the Essential Requirements of EU Directive 2006/42/EC** 89

Bibliography 90

Figures

Figure 1 — Example of boundary 14
Figure 2 — Jacking width 15
Figure 3 — Designation of ladder set sections 19
Figure 4 — Example of forces acting on turntable ladder 30
Figure 5 — Resulting force of the working load 31
Figure 6 — Surface exposed to the wind 32
Figure 7 — Minimum required residual force related to jacking width 34
Figure 8 — Maximum and minimum jacking width 35
Figure 9 — Test position without rescue cage 39
Figure 10 — Test position with rescue cage 39
Figure 11 — Static tilt angle δ for turntable ladders 48
Figure 12 — Maximum angle of elevation 50
Figure 13 — Relative positions of hand and guard-rails 52
Figure 14 — Impact simulation on the rescue cage 55
Figure 15 — Rung alignment 62
Figure 16 — Minimum dimensions of ladder sections 65
Figure 17 — Rung spacing dimensions 65
Figure 18 — Winding diameter 69
Figure 19 — Diagram of minimum unaffected zones 74
Figure 20 — Example of a warning label for the number of person permissible in the rescue cage 80

Tables

Table 1 — List of significant hazards 20
Table 2 — Safety factors for load calculations 32
Table 3 — Test cases for verification method 2 37
Table 4 — Functional Safety and Performance Level 56
Table 5 — Functional requirements for ladder set main control console 58
Table 6 — Dimensions 65
Table 7 — Determination of factor c 68
Table 8 — Determination of factor h_1 for the following construction unit 69
Table 9 — Determination of factor h_2 for the following construction unit 69
Table 10 — Nominal reaches 72
Table 11 — Overall maximum dimensions in travel position 73
Table 12 — Maximum gross laden mass 73
Table 13 — Masses taken into consideration in the calculation of gross laden mass 73
Table A.1 — Example of table reporting the stability tests 81
Table B.1 — Determination of the operating time 82
Table C.1 — Nominal reaches of turntable ladders in several European countries 83
Table D.1— Verifications and reception tests 85