

DIN EN 1866-2:2014-07 (E)

Mobile fire extinguishers - Part 2: R requirements for the construction, pressure resistance and mechanical tests for extinguishers, with a maximum allowable pressure equal to or lower than 30 bar, which comply with the requirements of EN 1866-1

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	5
4	Symbols and abbreviations	5
5	Materials	6
6	Design and prototype testing	6
6.1	Calculation design method	6
6.2	Experimental design method	6
6.3	Prototype testing	7
6.4	Macroscopic examination	8
6.5	Attached parts	8
6.6	Overfill pressure test	8
6.7	Requirements for components subject to pressure	8
6.8	Hose assembly and attached components	8
6.9	Propellant gas cylinders	9
7	Manufacturing	9
7.1	General requirements	9
7.2	Welded and brazed parts	9
7.3	Traceability	9
7.4	Marking	10
8	Inspection and testing during manufacturing	10
8.1	Assemblies	10
8.2	Extinguisher bodies	10
8.3	Accessories and fittings (excluding pressure relief devices)	11
8.4	Final inspection	11
Annex A (informative)	Classification of the different parts of an extinguisher subject to internal pressure	12
Annex B (normative)	Specifications for plastics components (except hoses, pistols and nozzles) ...	13
B.1	General	13
B.2	Requirements for plastics components subject to pressure	13
Annex C (normative)	Pressures and temperatures	16
Annex D (normative)	Overfill Pressure Test	17
Annex E (normative)	Test for burst pressure of hose assembly and attached components	18

Annex F (normative) Propellant gas cylinders	19
F.1 General requirements	19
F.2 Cylinder	19
F.3 Cylinder valve	19
F.4 Marking	19
Annex G (normative) Materials - quality control documents	21
Annex ZA (informative) Relationship between this European Standard and the essential requirements of EU Directive 97/23/EC	22