DIN EN 1866-2:2014-07 (E)

Mobile fire extinguishers - Part 2: R equirements for the construction, pressure resistance and mechanical tests for extinguishers, with a maximum allowable pressure equal to or lower than 30 bar, which comply with the requirements of EN 1866-1

Contents

Page

Foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 5

4 Symbols and abbreviations 5

5 Materials 6

6 Design and prototype testing 6
6.1 Calculation design method 6
6.2 Experimental design method 6
6.3 Prototype testing 7
6.4 Macroscopic examination 8
6.5 Attached parts 8
6.6 Overfill pressure test 8
6.7 Requirements for components subject to pressure 8
6.8 Hose assembly and attached components 8
6.9 Propellant gas cylinders 9

7 Manufacturing 9
7.1 General requirements 9
7.2 Welded and brazed parts 9
7.3 Traceability 9
7.4 Marking 10

8 Inspection and testing during manufacturing 10
8.1 Assemblies 10
8.2 Extinguisher bodies 10
8.3 Accessories and fittings (excluding pressure relief devices) 11
8.4 Final inspection 11

Annex A (informative) Classification of the different parts of an extinguisher subject to internal pressure 12

Annex B (normative) Specifications for plastics components (except hoses, pistols and nozzles) ... 13

B.1 General 13
B.2 Requirements for plastics components subject to pressure 13

Annex C (normative) Pressures and temperatures 16

Annex D (normative) Overfill Pressure Test 17

Annex E (normative) Test for burst pressure of hose assembly and attached components 18

Annex F (normative) Propellant gas cylinders 19

F.1 General requirements 19
F.2 Cylinder 19
F.3 Cylinder valve 19
F.4 Marking 19

Annex G (normative) Materials - quality control documents 21

Annex ZA (informative) Relationship between this European Standard and the essential requirements of EU Directive 97/23/EC 22