

# DIN EN 694:2014-10 (E)

## Fire-fighting hoses - Semi-rigid hoses for fixed systems

---

<b>Contents</b>		<b>Page</b>
Foreword .....		3
Introduction .....		4
<b>1</b>	<b>Scope .....</b>	<b>5</b>
<b>2</b>	<b>Normative references .....</b>	<b>5</b>
<b>3</b>	<b>Terms and Definitions .....</b>	<b>5</b>
<b>4</b>	<b>Classification .....</b>	<b>6</b>
<b>4.1</b>	<b>General .....</b>	<b>6</b>
<b>4.2</b>	<b>Classification by types (hose construction) .....</b>	<b>6</b>
<b>4.3</b>	<b>Classification by class (materials for lining and cover) .....</b>	<b>6</b>
<b>5</b>	<b>Dimensions, tolerances and maximum mass .....</b>	<b>6</b>
<b>5.1</b>	<b>Inside diameter and maximum mass .....</b>	<b>6</b>
<b>5.2</b>	<b>Length and tolerances on length .....</b>	<b>7</b>
<b>6</b>	<b>Performance requirements of finished hose .....</b>	<b>7</b>
<b>6.1</b>	<b>Hydrostatic requirements .....</b>	<b>7</b>
<b>6.1.1</b>	<b>Deformation under maximum working pressure .....</b>	<b>7</b>
<b>6.1.2</b>	<b>Deformation under proof pressure .....</b>	<b>8</b>
<b>6.1.3</b>	<b>Minimum burst pressure .....</b>	<b>8</b>
<b>6.1.4</b>	<b>Kink pressure .....</b>	<b>8</b>
<b>6.2</b>	<b>Adhesion .....</b>	<b>8</b>
<b>6.3</b>	<b>Accelerated ageing .....</b>	<b>8</b>
<b>6.4</b>	<b>Low temperature flexibility .....</b>	<b>9</b>
<b>6.5</b>	<b>Hot surface resistance .....</b>	<b>9</b>
<b>6.6</b>	<b>Ozone resistance .....</b>	<b>9</b>
<b>6.7</b>	<b>Bending and crush resistance .....</b>	<b>9</b>
<b>6.8</b>	<b>UV-resistance (xenon arc lamp) .....</b>	<b>9</b>
<b>6.9</b>	<b>Loss in mass on heating .....</b>	<b>9</b>
<b>7</b>	<b>Frequency of testing .....</b>	<b>9</b>
<b>8</b>	<b>Marking .....</b>	<b>10</b>
<b>Annex A (normative) Frequencies of testing (type test and production test) .....</b>		<b>11</b>
<b>Annex B (informative) Frequencies of testing (batch test) .....</b>		<b>12</b>
<b>Bibliography .....</b>		<b>13</b>