

DIN EN 54-31:2015-05 (E)

Fire detection and fire alarm system - Part 31: Multi-sensor fire detectors - Point detectors using a combination of smoke, carbon monoxide and optionally heat sensors

Contents		Page
Foreword		6
Introduction		8
1	Scope	9
2	Normative references	9
3	Terms and definitions	10
4	Requirements	10
4.1	General	10
4.2	Categorization	10
4.3	Nominal activation conditions/sensitivity	11
4.3.1	Individual alarm indication	11
4.3.2	Response to slowly developing fires, aging and contamination	11
4.3.3	Rate sensitive CO response	11
4.3.4	Repeatability of smoke response	11
4.3.5	Directional dependence of smoke response	12
4.3.6	Repeatability of CO response	12
4.3.7	Directional dependence of CO response	12
4.3.8	Directional dependence of heat response	12
4.3.9	Lower limit of heat response	12
4.3.10	Reproducibility of smoke response	12
4.3.11	Reproducibility of CO response	12
4.3.12	Reproducibility of heat response	12
4.3.13	Air movement	12
4.3.14	Dazzling	12
4.4	Operational reliability	13
4.4.1	Connection of ancillary devices	13
4.4.2	Monitoring of detachable detectors	13
4.4.3	Manufacturer's adjustments	13
4.4.4	On-site adjustment of response behaviour	13
4.4.5	Protection against the ingress of foreign bodies	13
4.4.6	Software controlled detectors	13
4.4.7	Long term stability	15
4.5	Tolerance to supply parameters - Variation in supply parameters	15
4.6	Performance parameters under fire conditions - Fire sensitivity	15
4.7	Durability of nominal activation conditions/sensitivity	15
4.7.1	Temperature resistance	15
4.7.2	Humidity resistance	15
4.7.3	Shock and vibration resistance	16
4.7.4	Electrical stability - EMC, immunity (operational)	16
4.7.5	Resistance to chemical agents	16
4.8	Detector sensitivity to single fire phenomena	16
4.8.1	Sensitivity to smoke	16
4.8.2	Sensitivity to carbon monoxide	17
4.8.3	Sensitivity to heat	17

5	Testing, assessment and sampling methods	17
5.1	General	17
5.1.1	Atmospheric conditions for tests	17
5.1.2	Operating conditions for tests	17
5.1.3	Mounting arrangements	17
5.1.4	Tolerances	17
5.1.5	Measurement of smoke response value	18
5.1.6	Measurement of CO response value	19
5.1.7	Measurement of heat response value	19
5.1.8	Provision for tests	20
5.1.9	Test schedule	20
5.2	Nominal activation conditions/sensitivity	22
5.2.1	Individual alarm indication	22
5.2.2	Response to slowly developing fires, aging and contamination	22
5.2.3	Rate sensitive CO response	23
5.2.4	Repeatability of smoke response	23
5.2.5	Directional dependence of smoke response	23
5.2.6	Repeatability of CO response	24
5.2.7	Directional dependence of CO response	24
5.2.8	Directional dependence of heat response	25
5.2.9	Lower limit of heat sensitivity	25
5.2.10	Reproducibility of smoke response	26
5.2.11	Reproducibility of CO response	26
5.2.12	Reproducibility of heat response	26
5.2.13	Air movement	27
5.2.14	Dazzling	28
5.3	Operational reliability	28
5.3.1	Connection of ancillary devices	28
5.3.2	Monitoring of detachable detectors	29
5.3.3	Manufacturer's adjustments	29
5.3.4	On-site adjustment of behaviour	29
5.3.5	Protection against the ingress of foreign bodies	29
5.3.6	Software controlled devices	29
5.3.7	Long term stability	29
5.4	Tolerance to supply parameters	30
5.4.1	Variation in supply parameters	30
5.5	Performance parameters under fire conditions	30
5.5.1	Fire sensitivity	30
5.6	Durability of nominal activation conditions/sensitivity	33
5.6.1	Temperature resistance	33
5.6.2	Humidity resistance	36
5.6.3	Shock and vibration resistance	41
5.6.4	Electrical stability	45
5.6.5	Resistance to chemical agents	47
5.7	Non-response to single fire phenomena	50
5.7.1	Sensitivity to smoke	50
5.7.2	Sensitivity to carbon monoxide	51
5.7.3	Sensitivity to heat	51
6	Assessment and verification of constancy of performance (AVCP)	52
6.1	General	52
6.2	Type testing	52
6.2.1	General	52
6.2.2	Test samples, testing and compliance criteria	53
6.2.3	Test reports	53
6.3	Factory production control (FPC)	53
6.3.1	General	53
6.3.2	Requirements	54
6.3.3	Product specific requirements	56
6.3.4	Initial inspection of factory and FPC	57
6.3.5	Continuous surveillance of FPC	57
6.3.6	Procedure for modifications	58

6.3.7	One-off products, pre-production products, (e.g. prototypes) and products produced in very low quantities	58
7	Classification and designation	59
8	Marking, Labelling and Packaging	59
Annex A (normative) Smoke tunnel for smoke response values		60
Annex B (normative) Test aerosol for smoke response value measurements		61
Annex C (normative) Smoke measuring instruments		62
C.1	Obscuration meter	62
C.2	Measuring ionization chamber (MIC)	62
Annex D (normative) Gas test chamber for CO response threshold value and cross-sensitivity to chemical agents		66
Annex E (normative) Heat tunnel for heat response value		67
Annex F (normative) Measuring instruments for CO		68
F.1	General	68
F.2	CO measuring instrument	68
Annex G (informative) Establishing exposure levels of chemical agents		69
G.1	General	69
G.2	Establishing concentration of chemical agents for test gases 1 to 9 of 5.6.5.3	69
G.3	Verification of test chamber leakage	69
G.4	Establishing concentration of ozone	69
Annex H (normative) Apparatus for dazzling test		70
Annex I (informative) Apparatus for impact test		72
Annex J (normative) Fire test room		74
Annex K (normative) Open wood fire (TF1)		76
K.1	Fuel	76
K.2	Arrangement	76
K.3	Method of ignition	76
K.4	Variables	76
K.5	End-of-test condition	76
K.6	Test validity criteria	76
Annex L (normative) Smouldering (pyrolysis) wood fire (TF2)		80
L.1	Fuel	80
L.2	Hotplate	80
L.3	Arrangement	80
L.4	Heating rate	80
L.5	End-of-test condition	80
L.6	Test validity criteria	80
Annex M (normative) Glowing smouldering cotton fire (TF3)		85
M.1	Fuel	85
M.2	Arrangement	85
M.3	Ignition	86

M.4	End-of-test condition	86
M.5	Test validity criteria	87
Annex N (normative) Open plastics (polyurethane) fire (TF4)		90
N.1	Fuel	90
N.2	Conditioning	90
N.3	Arrangement	90
N.4	Ignition	90
N.5	Method of ignition	90
N.6	End-of-test condition	90
N.7	Test validity criteria	90
Annex O (normative) Liquid (heptane) fire (TF5)		93
O.1	Fuel	93
O.2	Arrangement	93
O.3	Ignition	93
O.4	End-of-test condition	93
O.5	Test validity criteria	93
Annex P (normative) Low temperature black smoke (decalene) liquid fire (TF8)		96
P.1	Fuel	96
P.2	Arrangement	96
P.3	Ignition	96
P.4	End-of-test condition	96
P.5	Test validity criteria	96
Annex Q (informative) Information concerning the construction of the smoke tunnel		99
Annex R (informative) Information concerning the construction of the gas test chamber		102
Annex S (informative) Construction of the heat tunnel		104
Annex T (informative) Information concerning test procedures and requirements for response to slowly developing fires, aging and contamination		107
Annex U (informative) Information concerning the construction of the measuring ionization chamber		111
Bibliography		113