

# ISO 6182-12:2014-12 (E)

## Fire protection - Automatic sprinkler systems - Part 12: Requirements and test methods for grooved-end components for steel pipe systems

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	2
4	Product consistency .....	2
5	Product assembly .....	2
6	Requirements .....	3
6.1	Standard grooved-end dimensions .....	3
6.2	Minimum pipe wall thickness .....	3
6.3	Mechanical coupling housing .....	3
6.4	Pressure-responsive gasket .....	3
6.5	Bolts .....	3
6.6	Nuts .....	8
6.7	Hinge pins .....	8
6.8	Flexible coupling .....	8
6.9	Vacuum (see 7.2) .....	8
6.10	Air leakage (see 7.3) .....	8
6.11	Low-temperature exposure (see 7.4) .....	8
6.12	Heat ageing (see 7.5) .....	8
6.13	Hydrostatic pressure (see 7.6) .....	8
6.14	Bending moment (see 7.7) .....	8
6.15	Gasket material evaluation .....	8
6.16	Fire resistance (see 7.8) .....	9
6.17	Rated working pressure .....	9
6.18	Nominal sizes .....	9
7	Test methods .....	9
7.1	Test assembly .....	9
7.2	Vacuum (see 6.9) .....	9
7.3	Air leakage (see 6.10) .....	10
7.4	Low-temperature exposure (see 6.11) .....	10
7.5	Heat aging (see 6.12) .....	10
7.6	Hydrostatic pressure test (see 6.13) .....	11
7.7	Bending moment (see 6.14) .....	11
7.8	Fire resistance (see 6.16) .....	15
8	Markings .....	15
8.1	Housing markings .....	15
8.2	Gasket markings .....	15
8.3	Manufacturer's installation instructions .....	16