

DIN EN 54-29:2015-06 (E)

Fire detection and fire alarm systems - Part 29: Multi-sensor fire detectors - Point detectors using a combination of smoke and heat sensors

Contents		Page
Foreword		6
Introduction		8
1	Scope	9
2	Normative references	9
3	Terms and definitions	10
4	Requirements	10
4.1	General	10
4.2	Nominal activation conditions/sensitivity	10
4.2.1	Individual alarm indication	10
4.2.2	Response to slowly developing fires	10
4.2.3	Repeatability of smoke response	11
4.2.4	Directional dependence of smoke response	11
4.2.5	Directional dependence of heat response	11
4.2.6	Lower limit of heat response	11
4.2.7	Reproducibility of smoke response	11
4.2.8	Reproducibility of heat response	11
4.2.9	Air movement	11
4.2.10	Dazzling	11
4.3	Operational reliability	11
4.3.1	Connection of ancillary devices	11
4.3.2	Monitoring of detachable detectors	11
4.3.3	Manufacturer's adjustments	12
4.3.4	On-site adjustment of response behaviour	12
4.3.5	Protection against the ingress of foreign bodies	12
4.3.6	Software controlled detectors	12
4.4	Tolerance to supply parameters	13
4.4.1	Variation in supply parameters	13
4.5	Performance parameters under fire conditions	14
4.5.1	Fire sensitivity	14
4.6	Durability of nominal activation conditions/sensitivity	14
4.6.1	Temperature resistance	14
4.6.2	Humidity resistance	14
4.6.3	Shock and vibration resistance	14
4.6.4	Electrical stability	15
4.6.5	Resistance to chemical agents	15
5	Test and assessment and sampling methods	15
5.1	General	15
5.1.1	Atmospheric conditions for tests	15
5.1.2	Operating conditions for tests	15
5.1.3	Mounting arrangements	15
5.1.4	Tolerances	16
5.1.5	Measurement of smoke response value	16
5.1.6	Measurement of heat response value	16
5.1.7	Provision for tests	17
5.1.8	Test schedule	17

5.2	Nominal activation conditions/sensitivity	18
5.2.1	Individual alarm indication	18
5.2.2	Response to slowly developing fires	19
5.2.3	Repeatability of smoke response	19
5.2.4	Directional dependence of smoke response	19
5.2.5	Directional dependence of heat response	20
5.2.6	Lower limit of heat sensitivity	20
5.2.7	Reproducibility of smoke response	21
5.2.8	Reproducibility of heat response	21
5.2.9	Air movement	22
5.2.10	Dazzling	22
5.3	Operational reliability	23
5.3.1	Connection of ancillary devices	23
5.3.2	Monitoring of detachable detectors	23
5.3.3	Manufacturer's adjustments	23
5.3.4	On-site adjustment of behaviour	23
5.3.5	Protection against the ingress of foreign bodies	23
5.3.6	Software controlled devices	23
5.4	Tolerance to supply parameters	24
5.4.1	Variation in supply parameters	24
5.5	Performance parameters under fire conditions	24
5.5.1	Fire sensitivity	24
5.6	Durability of nominal activation conditions/sensitivity	26
5.6.1	Temperature resistance	26
5.6.2	Humidity resistance	28
5.6.3	Shock and vibration resistance	30
5.6.4	Electrical stability	34
5.6.5	Resistance to chemical agents	35
6	Assessment and verification of constancy of performance (AVCP)	37
6.1	General	37
6.2	Type testing	37
6.2.1	General	37
6.2.2	Test samples, testing and compliance criteria	38
6.2.3	Test reports	38
6.3	Factory production control (FPC)	38
6.3.1	General	38
6.3.2	Requirements	39
6.3.3	Product specific requirements	41
6.3.4	Initial inspection of factory and FPC	42
6.3.5	Continuous surveillance of FPC	42
6.3.6	Procedure for modifications	42
6.3.7	One-off products, pre-production products, (e.g. prototypes) and products produced in very low quantities	43
7	Classification and designation	43
8	Marking, Labelling and Packaging	44
	Annex A (normative) Smoke tunnel for smoke response values	45
	Annex B (normative) Test aerosol for smoke response value measurements	46
	Annex C (normative) Smoke measuring instruments	47
C.1	Obscuration meter	47
C.2	Measuring ionization chamber (MIC)	47
	Annex D (normative) Heat tunnel for heat response value	51
	Annex E (normative) Apparatus for dazzling test	52

Annex F (informative) Apparatus for impact test	54
Annex G (normative) Fire test room	56
Annex H (normative) Open wood fire (TF1)	58
H.1 Fuel	58
H.2 Arrangement	58
H.3 Method of ignition	58
H.4 Variables	58
H.5 End-of-test condition	58
H.6 Test validity criteria	59
Annex I (normative) Smouldering (pyrolysis) wood fire (TF2)	61
I.1 Fuel	61
I.2 Hotplate	61
I.3 Arrangement	61
I.4 Heating rate	61
I.5 End-of-test condition	61
I.6 Test validity criteria	61
Annex J (normative) Glowing smouldering cotton fire (TF3)	65
J.1 Fuel	65
J.2 Arrangement	65
J.3 Ignition	66
J.4 End-of-test condition	67
J.5 Test validity criteria	67
Annex K (normative) Open plastics (polyurethane) fire (TF4)	69
K.1 Fuel	69
K.2 Conditioning	69
K.3 Arrangement	69
K.4 Ignition	69
K.5 Method of ignition	69
K.6 End-of-test condition	69
K.7 Test validity criteria	69
Annex L (normative) Liquid (heptane) fire (TF5)	71
L.1 Fuel	71
L.2 Arrangement	71
L.3 Ignition	71
L.4 End-of-test condition	71
L.5 Test validity criteria	71
Annex M (normative) Low temperature black smoke (decalene) liquid fire (TF8)	73
M.1 Fuel	73
M.2 Arrangement	73
M.3 Ignition	73
M.4 End-of-test condition	73
M.5 Test validity criteria	73
Annex N (informative) Information concerning the construction of the smoke tunnel	75
Annex O (informative) Construction of the heat tunnel	77
Annex P (informative) Information concerning test procedures and requirements for the response to slowly developing fires	80

Annex Q (informative) Information concerning the construction of the measuring ionization chamber	84
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation	86
ZA.1 Scope and relevant characteristics	86
ZA.2 Procedure for assessment and verification of constancy of performance (AVCP) of point detectors using a combination of smoke and heat sensors	88
ZA.3 CE marking and labelling	92
Bibliography	96