

DIN EN 54-30:2015-11 (E)

Fire detection and fire alarm systems - Part 30: Multi-sensor fire detectors - Point detectors using a combination of carbon monoxide and heat sensors

Contents	Page
Foreword	6
Introduction	8
1 Scope	9
2 Normative references	9
3 Terms, definitions and abbreviations	10
3.1 Terms and definitions	10
3.2 Abbreviations	10
4 Requirements	10
4.1 General	10
4.2 Nominal activation conditions/sensitivity	10
4.2.1 Individual alarm indication	10
4.2.2 Rate sensitive CO response	11
4.2.3 Response to slowly developing fires	11
4.2.4 Repeatability of CO response	11
4.2.5 Directional dependence of CO response	11
4.2.6 Directional dependence of heat response	11
4.2.7 Lower limit of heat response	11
4.2.8 Reproducibility of CO response	11
4.2.9 Reproducibility of heat response	11
4.2.10 Air movement	11
4.3 Operational reliability	12
4.3.1 Connection of ancillary devices	12
4.3.2 Monitoring of detachable detectors	12
4.3.3 Manufacturer's adjustments	12
4.3.4 On-site adjustment of behaviour	12
4.3.5 Software-controlled detectors	12
4.3.6 Long-term stability	13
4.4 Tolerance to supply voltage -- Variation in supply parameters	14
4.5 Performance parameters under fire conditions -- Fire sensitivity	14
4.6 Durability of nominal activation/sensitivity	14
4.6.1 Temperature resistance	14
4.6.2 Humidity resistance	14
4.6.3 Corrosion resistance -- SO ₂ corrosion (endurance)	14
4.6.4 Shock and vibration resistance	15
4.6.5 Electrical stability -- EMC, immunity (operational)	15
4.6.6 Resistance to chemical agents	15
5 Test and evaluation methods	15
5.1 General	15
5.1.1 Atmospheric conditions for tests	15
5.1.2 Operating conditions for tests	16
5.1.3 Mounting arrangements	16
5.1.4 Tolerances	16
5.1.5 Measurement of CO response value	16
5.1.6 Measurement of heat response value	17
5.1.7 Provision for tests	17

5.1.8	Test schedule	18
5.2	Nominal activation conditions/sensitivity	19
5.2.1	Individual alarm indication	19
5.2.2	Rate sensitive CO response	19
5.2.3	Response to slowly developing fire	19
5.2.4	Repeatability of CO response	20
5.2.5	Directional dependence of CO response	20
5.2.6	Directional dependence of heat response	21
5.2.7	Lower limit of heat response	21
5.2.8	Reproducibility of CO response	22
5.2.9	Reproducibility of heat response	22
5.2.10	Air movement	23
5.3	Operational reliability	23
5.3.1	Connection of ancillary devices	23
5.3.2	Monitoring of detachable detectors	23
5.3.3	Manufacturer's adjustments	23
5.3.4	On-site adjustment of behaviour	23
5.3.5	Software controlled devices	23
5.3.6	Long-term stability (operational)	24
5.4	Tolerance to supply voltage -- Variations in supply parameters	24
5.4.1	Object	24
5.4.2	Test procedure	24
5.4.3	Requirements	24
5.5	Performance parameters under fire conditions -- Fire sensitivity	25
5.5.1	Object	25
5.5.2	Principle	25
5.5.3	Test procedure	25
5.5.4	Requirements	27
5.6	Durability	27
5.6.1	Temperature resistance	27
5.6.2	Humidity resistance	30
5.6.3	Corrosion resistance -- Sulphur dioxide SO₂ corrosion (endurance)	34
5.6.4	Shock and vibration resistance	35
5.6.5	Electrical stability -- EMC, immunity (operational)	39
5.6.6	Resistance to chemical agents	41
6	Assessment and verification of constancy of performance (AVCP)	43
6.1	General	43
6.2	Type testing	43
6.2.1	General	43
6.2.2	Test samples, testing and compliance criteria	44
6.2.3	Test reports	44
6.3	Factory production control (FPC)	44
6.3.1	General	44
6.3.2	Requirements	45
6.3.3	Product specific requirements	47
6.3.4	Initial inspection of factory and FPC	48
6.3.5	Continuous surveillance of FPC	48
6.3.6	Procedure for modifications	49
6.3.7	One-off products, pre-production products, (e.g. prototypes) and products produced in very low quantities	49
7	Classification	50
8	Marking, labelling and packaging	50
	Annex A (normative) Gas test chamber for CO response value and cross-sensitivity to chemical agents	51
A.1	General	51
A.2	Gas test chamber specification	51

Annex B (normative) Fire test room	52
B.1 General	52
B.2 Fire test room specification	52
Annex C (normative) Measuring instruments for smoke and CO	55
C.1 General	55
C.2 CO measuring instrument	55
C.3 Obscuration meter	55
C.4 Measuring ionization chamber (MIC)	55
Annex D (informative) Establishing exposure levels of chemical agents	56
D.1 General	56
D.2 Establishing concentration of chemical agents for test gases 1 to 9 of 5.23	56
D.3 Verification of test chamber leakage	56
D.4 Establishing concentration of ozone	56
Annex E (normative) Heat tunnel for heat response value	58
E.1 General	58
E.2 Heat tunnel specification	58
Annex F (normative) Smouldering (pyrolysis) wood fire (TF2)	59
F.1 General	59
F.2 Fuel	59
F.3 Hotplate	59
F.4 Arrangement	59
F.5 Heating rate	59
F.6 End-of-test condition	59
F.7 Test validity criteria	60
Annex G (normative) Glowing smouldering cotton fire (TF3)	64
G.1 Introduction	64
G.2 Fuel	64
G.3 Arrangement	64
G.4 Ignition	65
G.5 End-of-test condition	66
G.6 Test validity criteria	66
Annex H (normative) Open plastics (polyurethane) fire (TF4)	70
H.1 Introduction	70
H.2 Fuel	70
H.3 Conditioning	70
H.4 Arrangement	70
H.5 Ignition	70
H.6 Method of ignition	70
H.7 End-of-test condition	70
H.8 Test validity criteria	71
Annex I (normative) Liquid (heptane) fire (TF5)	74
I.1 Introduction	74
I.2 Fuel	74
I.3 Arrangement	74
I.4 Ignition	74
I.5 End-of-test condition	74
I.6 Test validity criteria	74

Annex J (informative) Information concerning the construction of the gas test chamber	78
J.1 General	78
J.2 Construction of the gas test chamber	78
Annex K (informative) Construction of the heat tunnel	80
K.1 General	80
K.2 Construction of the heat tunnel	80
Annex L (informative) Apparatus for impact test	84
L.1 General	84
L.2 Impact apparatus construction	84
Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Regulation	87
Bibliography	97