

DIN EN 54-7:2018-10 (E)

Fire detection and fire alarm systems - Part 7: Smoke detectors - Point smoke detectors that operate using scattered light, transmitted light or ionization

Contents		Page
European foreword		5
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Requirements	8
4.1	Compliance	8
4.2	Operational reliability	8
4.2.1	Individual alarm indication	8
4.2.2	Connection of ancillary devices	8
4.2.3	Monitoring of detachable detectors	8
4.2.4	Manufacturer's adjustments	9
4.2.5	On-site adjustment of response behaviour	9
4.2.6	Protection against the ingress of foreign bodies	9
4.2.7	Response to slowly developing fires	9
4.2.8	Software controlled detector (when provided)	10
4.3	Nominal activation conditions/sensitivity	11
4.3.1	Repeatability	11
4.3.2	Directional Dependence	11
4.3.3	Reproducibility	11
4.4	Response delay (response time)	11
4.4.1	Air movement	11
4.4.2	Dazzling	12
4.5	Tolerance to supply voltage -- Variation in supply parameters	12
4.6	Performance parameters under fire conditions -- Fire sensitivity	12
4.7	Durability of Nominal activation conditions/sensitivity	12
4.7.1	Temperature resistance	12
4.7.2	Humidity resistance	12
4.7.3	Corrosion resistance -- Sulfur dioxide (SO ₂) corrosion (endurance)	12
4.7.4	Vibration resistance	13
4.7.5	Electrical stability -- Electromagnetic Compatibility (EMC), Immunity tests (operational) ..	13
5	Testing, assessment and sampling methods	13
5.1	General	13
5.1.1	Atmospheric conditions for tests	13
5.1.2	Operating conditions for tests	13
5.1.3	Mounting arrangements	14
5.1.4	Tolerances	14
5.1.5	Measurement of response value	14
5.1.6	Provision for tests	15
5.1.7	Test schedule	15
5.2	Operational reliability	17
5.2.1	Individual alarm indication	17
5.2.2	Connection of ancillary devices	17
5.2.3	Monitoring of detachable detectors	17
5.2.4	Manufacturer's adjustments	17
5.2.5	On-site adjustment of response behaviour	17
5.2.6	Protection against the ingress of foreign bodies	17

5.2.7	Response to slowly developing fires	18
5.2.8	Software controlled detector (when provided)	18
5.3	Nominal activation conditions/sensitivity	18
5.3.1	Repeatability	18
5.3.2	Directional dependence	18
5.3.3	Reproducibility	19
5.4	Response delay (response time)	19
5.4.1	Air movement	19
5.4.2	Dazzling	20
5.5	Tolerance to supply voltage -- Variation in supply parameters	21
5.5.1	Object	21
5.5.2	Test procedure	21
5.5.3	Requirements	21
5.6	Performance parameters under fire conditions	21
5.6.1	Fire sensitivity	21
5.7	Durability of Nominal activation conditions/sensitivity	23
5.7.1	Temperature resistance	23
5.7.2	Humidity resistance	24
5.7.3	Corrosion resistance -- Sulfur dioxide (SO ₂) corrosion (endurance)	26
5.7.4	Vibration resistance	27
5.7.5	Electrical stability	31
6	Assessment and verification of constancy of performance (AVCP)	32
6.1	General	32
6.2	Type testing	32
6.2.1	General	32
6.2.2	Test samples, testing and compliance criteria	33
6.2.3	Test reports	33
6.3	Factory production control (FPC)	33
6.3.1	General	33
6.3.2	Requirements	34
6.3.3	Product specific requirements	36
6.3.4	Initial inspection of factory and FPC	37
6.3.5	Continuous surveillance of FPC	37
6.3.6	Procedure for modifications	37
6.3.7	One-off products, pre-production products, (e.g. prototypes) and products produced in very low quantities	38
7	Classification	38
8	Marking, labelling and packaging	38
	Annex A (normative) Smoke tunnel for response value measurements	40
	Annex B (normative) Test aerosol for response value measurements	41
	Annex C (normative) Smoke measuring instruments	42
C.1	Obscuration meter	42
C.2	Measuring ionization chamber (MIC)	42
C.2.1	General	42
C.2.2	Operating method and basic construction	43
C.2.3	Technical data	44
	Annex D (normative) Apparatus for dazzling test	46
	Annex E (informative) Apparatus for impact test	48
	Annex F (normative) Fire test room	50
	Annex G (normative) Smouldering (pyrolysis) wood fire (TF2)	52

G.1	Fuel	52
G.2	Hotplate	52
G.3	Arrangement	52
G.4	Heating rate	53
G.5	End of test condition	53
G.6	Test validity criteria	53
Annex H (normative) Glowing smouldering cotton fire (TF3)		55
H.1	Fuel	55
H.2	Arrangement	55
H.3	Ignition	55
H.4	End of test condition	56
H.5	Test validity criteria	56
Annex I (normative) Flaming plastics (polyurethane) fire (TF4)		57
I.1	Fuel	57
I.2	Arrangement	57
I.3	Ignition	57
I.4	End of test condition	57
I.5	Test validity criteria	57
Annex J (normative) Flaming liquid (n-heptane) fire (TF5)		59
J.1	Fuel	59
J.2	Arrangement	59
J.3	Ignition	59
J.4	End of test condition	59
J.5	Test validity criteria	59
Annex K (informative) Information concerning the construction of the smoke tunnel		61
Annex L (informative) Information concerning the requirements for the response to slowly developing fires		64
Annex M (informative) Information concerning the construction of the measuring ionization chamber		68
Annex N (normative) Test set-up for testing the protection against the effect of moving objects		71
Annex O (normative) Apparatus open detector static object test		73
Annex P (informative) Data supplied with point smoke detectors		74
Annex ZA (informative) Relationship of this European Standard with Regulation (EU) No.305/2011 ..		75
ZA.1	Scope and relevant characteristics	75
ZA.2	System of Assessment and Verification of Constancy of Performance (AVCP)	77
ZA.3	Assignment of AVCP tasks	77
Bibliography		79