# ISO 7240-5:2018 (E)

## Fire detection and fire alarm systems — Part 5: Point type heat detectors

# Contents


Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 General requirements

4.1 Compliance
4.2 Classification
4.3 Position of heat sensitive elements
4.4 Individual alarm indication
4.5 Connection of ancillary devices
4.6 Monitoring of detachable detectors
4.7 Manufacturer's adjustments
4.8 On-site adjustment of response behaviour
4.9 Requirements for software controlled detectors
4.9.1 General
4.9.2 Software design
4.9.3 The storage of programs and data

5 Tests

5.1 General
5.1.1 Atmospheric conditions for tests
5.1.2 Operating conditions for tests
5.1.3 Mounting arrangements
5.1.4 Tolerances
5.1.5 Measurement of response time
5.1.6 Provision for tests
5.1.7 Test schedule
5.2 Directional dependence
5.2.1 Object
5.2.2 Test procedure
5.2.3 Requirements
5.3 Static response temperature
5.3.1 Object
5.3.2 Test procedure
5.3.3 Requirements
5.4 Response times from typical application temperature
5.4.1 Object
5.4.2 Test procedure
5.4.3 Requirements
5.5 Response times from 25 °C
5.5.1 Object
5.5.2 Test procedure
5.5.3 Requirements
5.6 Response times from high ambient temperature (Dry heat operational)
5.6.1 Object
5.6.2 Test procedure
5.6.3 Requirements
5.7 Variation in supply parameters
5.7.1 Object

5.7.2 Test procedure
5.7.3 Requirements
5.8 Reproducibility
5.8.1 Object
5.8.2 Test procedure
5.8.3 Requirements
5.9 Cold (operational)
5.9.1 Object
5.9.2 Test procedure
5.9.2.1 Reference
5.9.2.2 State of the specimen(s) during conditioning
5.9.2.3 Conditioning
5.9.2.4 Measurements during conditioning
5.9.2.5 Final measurements
5.9.3 Requirements
5.10 Dry heat (endurance)
5.10.1 Object
5.10.2 Test procedure
5.10.2.1 Reference
5.10.2.2 State of the specimen during conditioning
5.10.2.3 Conditioning
5.10.2.4 Final measurements
5.10.3 Requirements
5.11 Damp heat, cyclic (operational)
5.11.1 Object
5.11.2 Test procedure
5.11.2.1 Reference
5.11.2.2 State of the specimen during conditioning
5.11.2.3 Conditioning
5.11.2.4 Measurements during conditioning
5.11.2.5 Final measurements
5.11.3 Requirements
5.12 Damp heat, steady state (endurance)
5.12.1 Object
5.12.2 Test procedure
5.12.2.1 Reference
5.12.2.2 State of the specimen(s) during conditioning
5.12.2.3 Conditioning
5.12.2.4 Final measurements
5.12.3 Requirements
5.13 Sulphur dioxide SO2 corrosion (endurance)
5.13.1 Object
5.13.2 Test procedure
5.13.2.1 Reference
5.13.2.2 State of the specimen during conditioning
5.13.2.3 Conditioning
5.13.2.4 Final measurements
5.13.3 Requirements
5.14 Shock (operational)
5.14.1 Object
5.14.2 Test procedure
5.14.2.1 Reference
5.14.2.2 State of the specimen during conditioning
5.14.2.3 Conditioning
5.14.2.4 Measurements during conditioning
5.14.2.5 Final measurements
5.14.3 Requirements
5.15 Impact (operational)
5.15.1 Object
5.15.2 Test procedure
5.15.2.1 Apparatus
5.15.2.2 State of the specimen during conditioning
5.15.2.3 Conditioning
5.15.2.4 Measurements during conditioning

5.15.2.5 Final measurements
5.15.3 Requirements
5.16 Vibration, sinusoidal, (operational)
5.16.1 Object
5.16.2 Test procedure
5.16.2.1 Reference
5.16.2.2 State of the specimen during conditioning
5.16.2.3 Conditioning
5.16.2.4 Measurements during conditioning
5.16.2.5 Final measurements
5.16.3 Requirements
5.17 Vibration, sinusoidal (endurance)
5.17.1 Object
5.17.2 Test procedure
5.17.2.1 Reference
5.17.2.2 State of the specimen during conditioning
5.17.2.3 Conditioning
5.17.2.4 Final measurements
5.17.3 Requirements
5.18 Electromagnetic Compatibility (EMC), Immunity tests (operational)
5.18.1 Test procedure
5.18.1.1 Reference
5.18.1.2 Final measurements
5.18.2 Requirements
5.19 Test for suffix S detectors
5.19.1 Object
5.19.2 Test procedure
5.19.2.1 Plunge test
5.19.2.2 Review of response time data
5.19.3 Requirements
5.20 Additional test for suffix R detector
5.20.1 Object
5.20.2 Test procedure
5.20.3 Requirements

6 Test report

7 Marking

8 Data

8.1 Hardware documentation
8.2 Software documentation

Annex A (normative) Heat tunnel for response time and response temperature measurements

Annex B (informative) Information concerning the construction of the heat tunnel

Annex C (informative) Derivation of upper and lower limits of response times

C.1 Upper limits
C.2 Lower limits
C.3 Change after environmental tests

Annex D (informative) Apparatus for impact test

Page count: 35