

ISO 7240-7:2018 (E)

Fire detection and alarm systems — Part 7: Point-type smoke detectors using scattered light, transmitted light or ionization

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	General requirements
4.1	Compliance
4.2	Response threshold value of detectors using scattered or transmitted light
4.3	Individual alarm indication
4.4	Connection of ancillary devices
4.5	Monitoring of detachable detectors
4.6	Manufacturer's adjustments
4.7	On-site adjustment of response behaviour
4.8	Protection against the ingress of foreign bodies
4.8.1	Closed detectors
4.8.2	Open detectors
4.9	Response to slowly developing fires
4.10	Requirements for software-controlled detectors
4.10.1	General
4.10.2	Software design
4.10.3	Storage of programs and data
5	Tests
5.1	General
5.1.1	Atmospheric conditions for tests
5.1.2	Operating conditions for tests
5.1.3	Mounting arrangements
5.1.4	Tolerances
5.1.5	Measurement of response threshold value
5.1.6	Provision for tests
5.1.7	Test schedule
5.1.8	Test report
5.2	Repeatability
5.2.1	Object of test
5.2.2	Test procedure
5.2.3	Requirements
5.3	Directional dependence
5.3.1	Object of test
5.3.2	Test procedure
5.3.3	Requirements
5.4	Reproducibility
5.4.1	Object of test
5.4.2	Test procedure
5.4.3	Requirements
5.5	Variation in supply parameters
5.5.1	Object of test
5.5.2	Test procedure
5.5.3	Requirements

5.6	Air movement
5.6.1	Object of test
5.6.2	Test procedure
5.6.3	Requirements
5.7	Dazzling
5.7.1	Object of test
5.7.2	Test procedure
5.7.3	Requirements
5.8	Additional tests for open detectors
5.8.1	Object of the test
5.8.2	Test procedure
5.9	Dry heat (operational)
5.9.1	Object of test
5.9.2	Test procedure
5.9.2.1	Reference
5.9.2.2	State of specimen during conditioning
5.9.2.3	Conditioning
5.9.2.4	Measurements during conditioning
5.9.2.5	Final measurements
5.9.3	Requirements
5.10	Cold (operational)
5.10.1	Object of test
5.10.2	Test procedure
5.10.2.1	Reference
5.10.2.2	State of specimen during conditioning
5.10.2.3	Conditioning
5.10.2.4	Measurements during conditioning
5.10.2.5	Final measurements
5.10.3	Requirements
5.11	Damp heat, steady state (operational)
5.11.1	Object of test
5.11.2	Test procedure
5.11.2.1	Reference
5.11.2.2	State of the specimen during conditioning
5.11.2.3	Conditioning
5.11.2.4	Measurements during conditioning
5.11.2.5	Final measurements
5.11.3	Requirements
5.12	Damp heat, steady state (endurance)
5.12.1	Object of test
5.12.2	Test procedure
5.12.2.1	Reference
5.12.2.2	State of the specimen during conditioning
5.12.2.3	Conditioning
5.12.2.4	Final measurements
5.12.3	Requirements
5.13	Sulfur dioxide (SO ₂) corrosion (endurance)
5.13.1	Object of test
5.13.2	Test procedure
5.13.2.1	Reference
5.13.2.2	State of specimen during conditioning
5.13.2.3	Conditioning
5.13.2.4	Final measurements
5.13.3	Requirements
5.14	Shock (operational)
5.14.1	Object of test
5.14.2	Test procedure
5.14.2.1	Reference
5.14.2.2	State of specimen during conditioning
5.14.2.3	Conditioning
5.14.2.4	Measurements during conditioning
5.14.2.5	Final measurements
5.14.3	Requirements
5.15	Impact (operational)

5.15.1	Object of test
5.15.2	Test procedure
5.15.2.1	Apparatus
5.15.2.2	State of specimen during conditioning
5.15.2.3	Conditioning
5.15.2.4	Measurements during conditioning
5.15.2.5	Final measurements
5.15.3	Requirements
5.16	Vibration, sinusoidal, (operational)
5.16.1	Object of test
5.16.2	Test procedure
5.16.2.1	Reference
5.16.2.2	State of specimen during conditioning
5.16.2.3	Conditioning
5.16.2.4	Measurements during conditioning
5.16.2.5	Final measurements
5.16.3	Requirements
5.17	Vibration, sinusoidal (endurance)
5.17.1	Object of test
5.17.2	Test procedure
5.17.2.1	Reference
5.17.2.2	State of specimen during conditioning
5.17.2.3	Conditioning
5.17.2.4	Final measurements
5.17.3	Requirements
5.18	Electromagnetic compatibility (EMC) immunity tests (operational)
5.19	Fire sensitivity
5.19.1	Object of test
5.19.2	Test procedure
5.19.2.1	Principle of test
5.19.2.2	Test fires
5.19.2.3	Mounting of specimens
5.19.2.4	Initial conditions
5.19.2.5	Recording of the fire parameters and response values
5.19.3	Requirements
6	Test report
7	Marking
8	Data
8.1	Hardware documentation
8.2	Software documentation
Annex A	(normative) Smoke tunnel for response threshold value measurements
Annex B	(normative) Test aerosol for response threshold value measurements
Annex C	(normative) Smoke-measuring instruments
C.1	Obscuration meter
C.2	Measuring ionization chamber (MIC)
C.2.1	General
C.2.2	Operating method and basic construction
C.2.3	Technical data
Annex D	(normative) Apparatus for dazzling test
Annex E	(normative) Apparatus for impact test
Annex F	(normative) Fire test room
Annex G	(normative) Smouldering (pyrolysis) wood fire (TF2)
G.1	Fuel
G.2	Hotplate

- G.3 Arrangement
- G.4 Heating rate
- G.5 End-of-test condition
- G.6 Test validity criteria

Annex H (normative) Glowing smouldering cotton fire (TF3)

- H.1 Fuel
- H.2 Arrangement
- H.3 Ignition
- H.4 End-of-test condition
- H.5 Test validity criteria

Annex I (normative) Flaming plastics (polyurethane) fire (TF4)

- I.1 Fuel
- I.2 Arrangement
- I.3 Ignition
- I.4 End-of-test condition
- I.5 Test validity criteria

Annex J (normative) Flaming liquid (n-heptane) fire (TF5)

- J.1 Fuel
- J.2 Arrangement
- J.3 Ignition
- J.4 End-of-test condition
- J.5 Test validity criteria

Annex K (informative) Information concerning the construction of the smoke tunnel

Annex L (informative) Compensation for detector drift

- L.1 Principles of compensation for detector drift
- L.2 Linear compensation
- L.3 Stepwise compensation
- L.4 High-rate compensation
- L.5 Avoidance of the non-linear region

Annex M (informative) Information concerning the construction of the measuring ionization chamber

Annex N (normative) Apparatus for open detector static object test

- N.1 General
- N.2 Test apparatus

Annex O (normative) Apparatus for testing the protection against the effect of moving objects

- O.1 General
- O.2 Test apparatus