

DIN EN 12845:2020-11 (E)

Fixed firefighting systems - Automatic sprinkler systems - Design, installation and maintenance

| Contents | | Page |
|------------------------|--|-------------|
| European foreword..... | | 12 |
| Introduction | | 13 |
| 1 | Scope..... | 15 |
| 2 | Normative references..... | 15 |
| 3 | Terms and definitions | 16 |
| 4 | Contract planning and documentation..... | 24 |
| 4.1 | General..... | 24 |
| 4.2 | Initial considerations..... | 24 |
| 4.3 | Preliminary or estimating stage | 24 |
| 4.4 | Design stage | 25 |
| 4.4.1 | General..... | 25 |
| 4.4.2 | Summary schedule..... | 25 |
| 4.4.3 | Installation layout drawings | 25 |
| 4.4.4 | Water supply..... | 28 |
| 5 | Extent of sprinkler protection..... | 31 |
| 5.1 | Buildings and areas to be protected..... | 31 |
| 5.1.1 | General..... | 31 |
| 5.1.2 | Permitted exceptions within a building..... | 31 |
| 5.1.3 | Necessary exceptions..... | 31 |
| 5.2 | Storage in the open air | 31 |
| 5.3 | Fire resistant separation | 31 |
| 5.4 | Protection of concealed spaces | 32 |
| 5.5 | Height difference between the highest and lowest sprinklers..... | 32 |
| 6 | Classification of occupancies and fire hazards..... | 32 |
| 6.1 | General..... | 32 |
| 6.2 | Hazard classes | 32 |
| 6.2.1 | General..... | 32 |
| 6.2.2 | Light Hazard - LH | 32 |
| 6.2.3 | Ordinary Hazard - OH..... | 32 |
| 6.2.4 | High Hazard - HH | 33 |
| 6.3 | Storage | 34 |
| 6.3.1 | General..... | 34 |
| 6.3.2 | Storage Configuration..... | 34 |
| 7 | Hydraulic design criteria..... | 37 |
| 7.1 | LH, OH and HHP | 37 |
| 7.2 | High Hazard Storage - HHS..... | 38 |
| 7.2.1 | General..... | 38 |
| 7.2.2 | Ceiling or roof protection only | 38 |
| 7.2.3 | Intermediate level in-rack sprinklers | 39 |
| 7.3 | Pressure and flow requirements for pre-calculated systems..... | 41 |
| 7.3.1 | LH and OH systems | 41 |
| 7.3.2 | HHP and HHS systems without in-rack sprinklers..... | 42 |
| 8 | Water supplies | 44 |

| | | |
|--------|---|----|
| 8.1 | General | 44 |
| 8.1.1 | Duration | 44 |
| 8.1.2 | Continuity | 44 |
| 8.1.3 | Frost protection..... | 44 |
| 8.2 | Maximum water pressure..... | 44 |
| 8.3 | Connections for other services | 45 |
| 8.4 | Housing of equipment for water supplies | 46 |
| 8.5 | Test facility devices..... | 46 |
| 8.5.1 | General | 46 |
| 8.5.2 | At pump house | 47 |
| 8.5.3 | At control valve sets..... | 47 |
| 8.6 | Water supply test..... | 47 |
| 8.6.1 | General | 47 |
| 8.6.2 | Storage tank and pressure tank supplies | 47 |
| 8.6.3 | Town main, booster pump, elevated private reservoir and gravity tank supplies | 48 |
| 9 | Type of water supply | 48 |
| 9.1 | General | 48 |
| 9.2 | Town mains..... | 48 |
| 9.3 | Storage tanks..... | 48 |
| 9.3.1 | General | 48 |
| 9.3.2 | Water volume..... | 49 |
| 9.3.3 | Refill rates for full capacity tanks..... | 50 |
| 9.3.4 | Reduced capacity tanks | 50 |
| 9.3.5 | Effective capacity of tanks and dimensions of suction chambers | 52 |
| 9.3.6 | Strainers..... | 53 |
| 9.4 | Inexhaustible sources – settling and suction chambers | 53 |
| 9.5 | Pressure tanks | 56 |
| 9.5.1 | General | 56 |
| 9.5.2 | Housing..... | 56 |
| 9.5.3 | Minimum capacity (water)..... | 56 |
| 9.5.4 | Air pressure and contents | 56 |
| 9.5.5 | Charging with air and water | 57 |
| 9.5.6 | Control and safety equipment..... | 57 |
| 9.6 | Choice of water supply..... | 57 |
| 9.6.1 | Single water supplies | 57 |
| 9.6.2 | Superior single water supplies | 58 |
| 9.6.3 | Duplicate water supplies | 58 |
| 9.6.4 | Combined water supplies | 58 |
| 9.7 | Isolation of water supply | 59 |
| 10 | Pumps | 59 |
| 10.1 | General | 59 |
| 10.2 | Multiple pump arrangements | 59 |
| 10.3 | Compartments for pumpsets..... | 60 |
| 10.3.1 | General | 60 |
| 10.3.2 | Sprinkler protection..... | 60 |
| 10.3.3 | Temperature | 60 |
| 10.3.4 | Ventilation..... | 60 |
| 10.4 | Maximum temperature of water supply | 60 |
| 10.5 | Valves and accessories..... | 60 |
| 10.6 | Suction conditions..... | 61 |
| 10.6.1 | General | 61 |
| 10.6.2 | Suction pipe | 61 |

| | | |
|---------|--|----|
| 10.7 | Performance characteristics..... | 64 |
| 10.7.1 | Pre-calculated systems – LH and OH..... | 64 |
| 10.7.2 | Pre-calculated systems – HHP and HHS with no in-rack sprinklers..... | 65 |
| 10.7.3 | Calculated systems..... | 66 |
| 10.7.4 | Pressure and water capacity of boosted town mains..... | 67 |
| 10.7.5 | Pressure switches..... | 67 |
| 10.8 | Electrically driven pumpsets..... | 67 |
| 10.8.1 | General..... | 67 |
| 10.8.2 | Electricity supply..... | 67 |
| 10.8.3 | Main switchboard..... | 68 |
| 10.8.4 | Installation between the main switchboard and the pump controller..... | 68 |
| 10.8.5 | Pump controller..... | 69 |
| 10.8.6 | Monitoring of pump operation..... | 69 |
| 10.9 | Diesel engine driven pumpsets..... | 69 |
| 10.9.1 | General..... | 69 |
| 10.9.2 | Engines..... | 69 |
| 10.9.3 | Cooling system..... | 70 |
| 10.9.4 | Air filtration..... | 70 |
| 10.9.5 | Exhaust system..... | 70 |
| 10.9.6 | Fuel, fuel tank and fuel feed pipes..... | 70 |
| 10.9.7 | Starting mechanism..... | 71 |
| 10.9.8 | Electric starter motor batteries..... | 72 |
| 10.9.9 | Battery chargers..... | 72 |
| 10.9.10 | Siting of batteries and chargers..... | 72 |
| 10.9.11 | Starter alarm indication..... | 72 |
| 10.9.12 | Tools and spare parts..... | 73 |
| 10.9.13 | Engine tests and exercising..... | 73 |
| 11 | Installation type and size..... | 74 |
| 11.1 | Wet pipe installations..... | 74 |
| 11.1.1 | General..... | 74 |
| 11.1.2 | Protection against freezing..... | 74 |
| 11.1.3 | Size of installations..... | 74 |
| 11.2 | Dry pipe installations..... | 75 |
| 11.2.1 | General..... | 75 |
| 11.2.2 | Size of installations..... | 75 |
| 11.3 | Alternate installations..... | 75 |
| 11.3.1 | General..... | 75 |
| 11.3.2 | Size of installations..... | 76 |
| 11.4 | Pre-action installations..... | 76 |
| 11.4.1 | General..... | 76 |
| 11.4.2 | Automatic detection system..... | 76 |
| 11.4.3 | Size of installations..... | 77 |
| 11.5 | Subsidiary dry pipe or alternate extension..... | 77 |
| 11.5.1 | General..... | 77 |
| 11.5.2 | Size of subsidiary extensions..... | 77 |
| 11.6 | Subsidiary water spray extension..... | 77 |
| 12 | Spacing and location of sprinklers..... | 77 |
| 12.1 | General..... | 77 |
| 12.2 | Maximum area of coverage per sprinkler..... | 78 |
| 12.3 | Minimum distance between sprinklers..... | 80 |
| 12.4 | Location of sprinklers in relation to building construction..... | 80 |
| 12.5 | Intermediate sprinklers in HH occupancies..... | 86 |

| | | |
|--------|---|-----|
| 12.5.1 | General | 86 |
| 12.5.2 | Maximum vertical distance between sprinklers at intermediate levels | 86 |
| 12.5.3 | Horizontal position of sprinklers at intermediate levels | 86 |
| 12.5.4 | Numbers of rows of sprinklers at each level | 88 |
| 12.5.5 | HHS intermediate sprinklers in non-shelved racks | 88 |
| 12.5.6 | HHS intermediate sprinklers below solid or slatted shelves in racks (ST5 and ST6) | 89 |
| 13 | Pipe sizing and layout | 90 |
| 13.1 | General | 90 |
| 13.2 | Calculation of pressure losses in pipework | 90 |
| 13.2.1 | Pipe friction loss | 90 |
| 13.2.2 | Static pressure difference | 91 |
| 13.2.3 | Velocity | 91 |
| 13.2.4 | Pressure loss through fittings and valves | 91 |
| 13.2.5 | Accuracy of calculations | 92 |
| 13.3 | Pre-calculated systems | 93 |
| 13.3.1 | General | 93 |
| 13.3.2 | Location of Design Points | 93 |
| 13.3.3 | Light Hazard - LH | 94 |
| 13.3.4 | Ordinary Hazard - OH | 96 |
| 13.3.5 | High hazard - HHP and HHS (except intermediate level sprinklers) | 97 |
| 13.4 | Fully calculated systems | 106 |
| 13.4.1 | Design density | 106 |
| 13.4.2 | Locations of the area of operation | 107 |
| 13.4.3 | Shape of the area of operation | 107 |
| 13.4.4 | Minimum sprinkler discharge pressure | 110 |
| 13.4.5 | Minimum pipe diameters | 110 |
| 14 | Sprinkler design characteristics and uses | 111 |
| 14.1 | General | 111 |
| 14.2 | Sprinkler types and application | 111 |
| 14.2.1 | General | 111 |
| 14.2.2 | Ceiling, flush, recessed and concealed pattern | 112 |
| 14.2.3 | Sidewall pattern | 112 |
| 14.2.4 | Flat spray pattern | 112 |
| 14.3 | Flow from sprinklers | 112 |
| 14.4 | Sprinkler temperature ratings | 113 |
| 14.5 | Sprinkler thermal sensitivity | 114 |
| 14.5.1 | General | 114 |
| 14.5.2 | Interaction with other measures | 114 |
| 14.6 | Sprinkler guards | 114 |
| 14.7 | Sprinkler water shields | 114 |
| 14.8 | Sprinkler rosettes | 115 |
| 14.9 | Corrosion protection of sprinklers | 115 |
| 15 | Valves | 115 |
| 15.1 | Control valve set | 115 |
| 15.2 | Stop valves | 115 |
| 15.3 | Ring main valves | 115 |
| 15.4 | Drain valves | 115 |
| 15.5 | Test valves | 116 |
| 15.5.1 | Alarm and pump start test valves | 116 |
| 15.5.2 | Remote test valves | 117 |
| 15.6 | Flushing connections | 117 |
| 15.7 | Pressure gauges | 117 |

| | | |
|--------|---|-----|
| 15.7.1 | General..... | 117 |
| 15.7.2 | Water supply connections..... | 117 |
| 15.7.3 | Control valve set..... | 117 |
| 15.7.4 | Removal..... | 118 |
| 16 | Alarms and alarm devices..... | 118 |
| 16.1 | Water flow alarms..... | 118 |
| 16.1.1 | General..... | 118 |
| 16.1.2 | Water motor and gong..... | 118 |
| 16.1.3 | Piping to water motor..... | 118 |
| 16.2 | Electrical water flow and pressure switches | 118 |
| 16.2.1 | General..... | 118 |
| 16.2.2 | Water flow alarm switches..... | 118 |
| 16.2.3 | Dry and pre-action systems..... | 119 |
| 16.3 | Fire brigade and remote central station alarm connection..... | 119 |
| 17 | Pipework..... | 119 |
| 17.1 | General..... | 119 |
| 17.1.1 | Underground piping..... | 119 |
| 17.1.2 | Above ground piping..... | 119 |
| 17.1.3 | Welding of steel pipe..... | 119 |
| 17.1.4 | Flexible pipes and joints..... | 120 |
| 17.1.5 | Concealment..... | 120 |
| 17.1.6 | Protection against fire and mechanical damage..... | 120 |
| 17.1.7 | Painting..... | 120 |
| 17.1.8 | Drainage | 120 |
| 17.1.9 | Copper pipe | 121 |
| 17.2 | Pipe supports..... | 121 |
| 17.2.1 | General..... | 121 |
| 17.2.2 | Spacing and location | 121 |
| 17.2.3 | Design..... | 122 |
| 17.3 | Pipework in concealed spaces..... | 122 |
| 17.3.1 | General..... | 122 |
| 17.3.2 | False ceilings above OH occupancies | 122 |
| 17.3.3 | All other cases | 123 |
| 18 | Signs, notices, and information..... | 123 |
| 18.1 | Block plan | 123 |
| 18.2 | Signs and notices | 123 |
| 18.2.1 | Location plate | 123 |
| 18.2.2 | Signs for stop valves..... | 123 |
| 18.2.3 | Control valve set..... | 123 |
| 18.2.4 | Water supply connections to other services..... | 124 |
| 18.2.5 | Suction and booster pumps..... | 124 |
| 18.2.6 | Electric switches and control panels..... | 124 |
| 18.2.7 | Testing and operating devices..... | 125 |
| 19 | Commissioning..... | 125 |
| 19.1 | Commissioning tests | 125 |
| 19.1.1 | Pipework..... | 125 |
| 19.1.2 | Equipment | 125 |
| 19.1.3 | Water supplies | 126 |
| 19.2 | Completion certificate and documents | 126 |
| 20 | Maintenance..... | 126 |
| 20.1 | General..... | 126 |

| | | |
|--------|--|-----|
| 20.1.1 | Introduction..... | 126 |
| 20.1.2 | Programmed work..... | 126 |
| 20.1.3 | Precautions while carrying out work..... | 126 |
| 20.1.4 | Replacement sprinklers..... | 126 |
| 20.2 | User's programme of inspection and checking..... | 127 |
| 20.2.1 | General | 127 |
| 20.2.2 | Weekly routine..... | 127 |
| 20.2.3 | Monthly routine | 128 |
| 20.3 | Service, testing and maintenance schedule | 128 |
| 20.3.1 | General | 128 |
| 20.3.2 | Quarterly routine..... | 128 |
| 20.3.3 | Half-yearly routine..... | 129 |
| 20.3.4 | Yearly routine | 130 |
| 20.3.5 | 3 Yearly routine..... | 130 |
| 20.3.6 | 10 yearly routine | 131 |
| 21 | A1 Periodic system inspection..... | 131 |
| | Annex A (normative) Classification of typical hazards | 132 |
| | Annex B (normative) Methodology for categorizing stored goods | 135 |
| B.1 | General | 135 |
| B.2 | Material factor (M) | 135 |
| B.2.1 | General | 135 |
| B.2.2 | Material Factor 1 | 135 |
| B.2.3 | Material factor 2 | 136 |
| B.2.4 | Material factor 3 | 136 |
| B.2.5 | Material factor 4 | 137 |
| B.3 | Storage configuration | 137 |
| B.3.1 | Effect of storage configuration | 137 |
| B.3.2 | Exposed plastic container with non-combustible content | 138 |
| B.3.3 | Exposed plastic surface - unexpanded | 138 |
| B.3.4 | Exposed plastic surface - expanded | 138 |
| B.3.5 | Open structure | 138 |
| B.3.6 | Solid block materials | 139 |
| B.3.7 | Granular or powdered materials | 139 |
| B.3.8 | No special configuration | 139 |
| | Annex C (normative) Alphabetical listing of stored products and categories | 140 |
| | Annex D (normative) Zoning of sprinkler installations | 144 |
| D.1 | General | 144 |
| D.2 | Zoning of installations | 144 |
| D.3 | Requirements for zoned installations | 144 |
| D.3.1 | Extent of zones | 144 |
| D.3.2 | Zone subsidiary stop valves | 144 |

| | | |
|---------|--|-----|
| D.3.3 | Flushing Valves | 144 |
| D.3.4 | Monitoring..... | 144 |
| D.3.5 | Zone test and drainage facilities..... | 145 |
| D.3.6 | Installation control valve set | 145 |
| D.3.7 | Installation monitoring and alarms | 145 |
| D.4 | Block plan | 145 |
| Annex E | (normative) Special requirements for high rise systems..... | 147 |
| E.1 | General..... | 147 |
| E.2 | Design criteria..... | 147 |
| E.2.1 | Hazard group | 147 |
| E.2.2 | Subdivision of high rise sprinkler systems..... | 147 |
| E.2.3 | Standing water pressures at non-return and alarm valves | 147 |
| E.2.4 | Calculation of distribution pipework for pre-calculated systems..... | 147 |
| E.2.5 | Water pressures | 147 |
| E.3 | Water supplies | 148 |
| E.3.1 | Types of water supplies | 148 |
| E.3.2 | Pressure and flow requirements for pre-calculated installations..... | 148 |
| E.3.3 | Water supply characteristics for pre-calculated installations | 148 |
| E.3.4 | Pump performance for pre-calculated installations..... | 148 |
| Annex F | (normative) Additional measures to improve system reliability and availability | 151 |
| F.1 | General..... | 151 |
| F.2 | Subdivision into zones | 151 |
| F.3 | Wet pipe installations..... | 151 |
| F.4 | Sprinkler type and sensitivity | 151 |
| F.5 | Control valve set..... | 151 |
| F.6 | Water supplies | 151 |
| F.7 | Additional measures for theatres | 151 |
| F.8 | Additional precautions for maintenance | 152 |
| Annex G | (normative) Protection of special hazards..... | 153 |
| G.1 | General..... | 153 |
| G.2 | Aerosols | 153 |
| G.3 | Clothes in multiple garment hanging storage..... | 153 |
| G.3.1 | General..... | 153 |
| G.3.2 | Categorization | 154 |
| G.3.3 | Sprinkler protection other than at ceiling..... | 154 |
| G.3.4 | Sprinklers in operation..... | 154 |

| | | |
|----------------|---|------------|
| G.3.5 | Ceiling sprinklers | 154 |
| G.3.6 | Automatic shutdown | 154 |
| G.3.7 | Control valve set..... | 155 |
| G.4 | Flammable liquid storage..... | 155 |
| G.5 | Idle pallets..... | 157 |
| G.6 | Spirit based liquors in wooden barrels | 158 |
| G.7 | Non-woven synthetic fabric | 158 |
| G.7.1 | Free standing storage..... | 158 |
| G.7.2 | Rack storage | 159 |
| G.8 | Polypropylene or polyethylene storage bins..... | 159 |
| G.8.1 | General | 159 |
| G.8.2 | Classification | 159 |
| G.8.3 | Palletized rack storage (ST4) | 159 |
| G.8.4 | All other storage..... | 159 |
| G.8.5 | Foam additive..... | 160 |
| Annex H | (normative) Sprinkler systems monitoring..... | 161 |
| H.1 | General | 161 |
| H.2 | Functions to be monitored | 161 |
| H.2.1 | General | 161 |
| H.2.2 | Stop valves controlling water flow to sprinklers | 161 |
| H.2.3 | Other stop valves | 161 |
| H.2.4 | Liquid levels..... | 161 |
| H.2.5 | Pressures | 161 |
| H.2.6 | Electrical power | 162 |
| H.2.7 | Temperature | 162 |
| Annex I | (normative) Transmission of alarms | 163 |
| I.1 | Functions to be monitored | 163 |
| I.2 | Alarm levels | 164 |
| Annex J | (informative) Precautions and procedures when a system is not fully operational..... | 165 |
| J.1 | Minimizing the effects..... | 165 |
| J.2 | Planned shut-down | 165 |
| J.3 | Unplanned shut-down..... | 166 |
| J.4 | Action following sprinkler operation..... | 166 |
| J.4.1 | General | 166 |
| J.4.2 | Installations protecting cold storage warehouses (air circulation refrigeration) | 166 |
| Annex K | (informative) Twenty-five year inspection..... | 167 |

| | |
|--|------------|
| Annex L (informative) Special technology | 168 |
| Annex M (informative) Independent certification body | 169 |
| Annex N (normative) Control Mode Specific Application Sprinklers: CMSA | 170 |
| N.1 Introduction | 170 |
| N.1.1 General..... | 170 |
| N.1.2 Definitions | 170 |
| N.1.3 General..... | 170 |
| N.1.4 Sprinkler type and temperature rating | 170 |
| N.1.5 Water demand..... | 171 |
| N.2 Sprinkler location | 171 |
| N.2.1 Sprinkler spacing | 171 |
| N.2.2 Range pipe sizes..... | 171 |
| N.2.3 Minimum clear space below sprinklers..... | 171 |
| N.2.4 Excessive clearance | 171 |
| N.2.5 Distance of sprinklers below ceiling..... | 171 |
| N.2.6 Location of sprinklers in beam and girder, concrete T and panel construction..... | 172 |
| N.2.7 Obstructions to sprinkler distribution..... | 172 |
| N.3 Design..... | 176 |
| Annex O (informative) Example of P&ID | 182 |
| Annex P (normative) ESFR sprinkler protection | 183 |
| P.1 Introduction | 183 |
| P.2 Scope | 183 |
| P.3 Definitions | 183 |
| P.3.1 Sprinkler, ESFR pattern | 183 |
| P.3.2 Suppression mode | 183 |
| P.3.3 Classification of goods | 183 |
| P.3.4 Ceiling height..... | 184 |
| P.3.5 Laced tyre storage..... | 184 |
| P.3.6 Paper categories, based on weight | 184 |
| P.4 Contract arrangements | 184 |
| P.5 General..... | 184 |
| P.6 Occupancies and fire hazards | 185 |
| P.7 Racked, shelved and post pallet storage..... | 185 |
| P.7.1 Longitudinal and transverse flues | 185 |
| P.7.2 Shelving..... | 186 |
| P.7.3 In-rack sprinklers for ESFR systems | 186 |

| | | |
|-----------------------|--|-----|
| P.7.4 | Design requirements..... | 186 |
| P.8 | Building requirements | 205 |
| P.8.1 | Roof or ceiling slope | 205 |
| P.8.2 | Measures required to correct excessive roof or ceiling slope..... | 205 |
| P.8.3 | Ceiling strength | 206 |
| P.8.4 | Sky lights..... | 206 |
| P.8.5 | Powered ventilation | 206 |
| P.8.6 | Walkways and conveyors | 208 |
| P.8.7 | Sprinkler protection beneath mezzanines..... | 208 |
| P.9 | ESFR sprinkler installation design | 208 |
| P.9.1 | Installation type | 208 |
| P.9.2 | Sprinkler nominal k-factor | 208 |
| P.9.3 | Temperature ratings thermal sensitivity and colour codings | 208 |
| P.9.4 | ESFR sprinkler location relative to obstructions at or near the ceiling or roof..... | 209 |
| P.10 | Pipe sizing | 210 |
| P.10.1 | General | 210 |
| P.10.2 | Minimum pipe sizes | 210 |
| P.10.3 | Minimum ESFR sprinkler flow pressure | 210 |
| P.10.4 | The number of sprinklers assumed to be operating | 210 |
| P.10.5 | Shape of design sprinkler area | 211 |
| P.10.6 | Sprinklers beneath obstructions | 211 |
| P.11 | Sprinkler spacing and location | 211 |
| P.11.1 | ESFR sprinkler area of coverage | 211 |
| P.11.2 | Obstructions | 211 |
| P.11.3 | Sprinkler positioning relative to roof and ceilings | 212 |
| P.11.4 | Sprinkler orientation relative to the floor or pipework | 212 |
| P.11.5 | Clear space below sprinklers | 212 |
| P.11.6 | Sprinkler location relative to draught or smoke curtains..... | 212 |
| P.11.7 | Positioning of ESFR sprinklers relative to draught or smoke curtains..... | 212 |
| P.11.8 | ESFR sprinkler protection adjacent to areas protected by standard sprinklers..... | 212 |
| P.12 | Water supplies..... | 213 |
| P.12.1 | Pump drive and power arrangements | 213 |
| P.12.2 | Pump selection | 213 |
| P.12.3 | Duration..... | 213 |
| Annex Q (informative) | Ⓐ Periodic system inspection..... | 214 |
| Bibliography | | 215 |