ISO 6182-16:2020-05 (E)

Fire protection - Automatic sprinkler systems - Part 16: Requirements and test methods for fire pump relief valves

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Requirements 2
4.1 Nominal sizes and tolerances 2
4.2 Connections 2
4.3 Rated working pressure 2
4.4 Body and cover 2
4.5 Body strength (see 6.4) 3
4.6 Access for maintenance 3
4.7 Components 3
4.8 Leakage and deformation (see 6.3) 4
4.9 Non-metallic components (excluding gaskets, diaphragms, seals and other elastomeric parts) 4
4.10 Sealing assembly elements (see 6.7) 4
4.11 Clearances 4
4.12 Operation and reseat (see 6.8) 4
4.13 Flow capacity (see 6.9) 4
4.14 Endurance (see 6.10) 5

5 Production testing and quality control 5

6 Tests 5
6.1 Samples 5
6.2 Spring and diaphragm test (see 4.7.6 and 4.7.7) 6
6.3 Leakage and deformation (see 4.8) 6
6.3.1 Body leakage 6
6.3.2 Sealing assembly 6
6.4 Body strength (see 4.5) 6
6.5 Warm-water ageing test for non-metallic components (excluding gaskets, seals and other elastomeric components) 6
6.6 Air ageing test for non-metallic components (excluding gaskets, seals and other elastomeric components) 7
6.7 Sealing element tests (see 4.10) 7
6.8 Operational and reseat (see 4.12) 8
6.9 Flow capacity (see 4.13) 8
6.10 Endurance test (see 4.14) 8

7 Marking 8

8 Manufacturer's installation instructions 9

Annex A (normative) Tolerances 10

Bibliography 11