

ISO 6182-17:2020 (E)

Fire protection — Automatic sprinkler systems — Part 17: Requirements and test methods for pressure reducing valves

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Requirements
4.1	Nominal sizes and tolerances
4.2	Connections
4.3	Rated working pressure
4.4	Body and cover
4.5	Strength (see 6.4)
4.6	Access for maintenance
4.7	Components
4.8	Leakage and deformation (6.3)
4.9	Non-metallic components (excluding gaskets, diaphragms, seals and other elastomeric parts) (see 6.5 and 6.6)
4.10	Sealing assembly elements (see 6.7)
4.11	Clearances
4.12	Operation (see 6.8)
4.13	Static leakage (see 6.9)
4.14	Durability (see 6.10)
5	Production testing and quality control
6	Tests
6.1	Samples
6.2	Spring and diaphragm
6.2.1	Spring
6.2.1.1	General
6.2.1.2	Sealing assembly
6.2.1.3	Internal bypass
6.2.2	Diaphragm
6.3	Leakage and deformation (see 4.8)
6.3.1	Body leakage (see 4.8.1)
6.3.2	Sealing assembly (see 4.8.2)
6.3.3	Stem seal and repacking leakage (see 4.8.3)
6.4	Strength (see 4.5)
6.4.1	Body (see 4.5.1)
6.4.2	Diaphragms (see 4.5.2)
6.5	Warm-water ageing test for non-metallic components (excluding gaskets, seals and other elastomeric components) (see 4.9)
6.6	Air ageing test for non-metallic components (excluding gaskets, seals and other elastomeric components) (see 4.9)
6.7	Sealing element tests (see 4.10)
6.8	Operation (see 4.12)
6.9	Static leakage (90 days) (see 4.13)
6.10	Durability (see 4.14)
7	Marking
8	Manufacturer's installation instructions
Annex A	(normative) Tolerances