

ISO/TR 7240-9:2022-04 (E)

Fire detection and alarm systems - Part 9: Test fires for fire detectors

Contents		Page
Foreword		vi
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms, definitions and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Abbreviated terms	1
4	Characteristics of test fires	2
5	Test laboratory	3
5.1	General	3
5.2	Fire test room (for all detectors except aspirating smoke detectors)	3
5.3	Fire test room and ventilation system (for aspirating smoke detectors)	4
5.3.1	Fire test room	5
5.3.2	Ventilation system	6
5.4	Ambient test condition	7
5.5	Instruments	8
5.5.1	General	8
5.5.2	Obscuration meter	8
5.5.3	Measuring ionization chamber (MIC)	9
5.5.4	CO measuring instrument	11
5.5.5	Spark generator	12
6	Test method description	13
6.1	General	13
6.2	Arrangement	13
6.3	Measurement parameters	13
6.4	End-of-test parameters	13
7	Test fires	13
7.1	General	13
7.2	Test fire TF1 -- Open cellulosic (wood) fire	14
7.2.1	General	14
7.2.2	Fuel	14
7.2.3	Conditioning	14
7.2.4	Preparation	14
7.2.5	Arrangement	14
7.2.6	Ignition starter	15
7.2.7	Test validity criteria	15
7.2.8	End-of-test conditions	16
7.3	Test fire TF2 -- Smouldering (pyrolysis) wood fire	16
7.3.1	General	16
7.3.2	Fuel	16
7.3.3	Hotplate	16
7.3.4	Arrangement	16
7.3.5	Heating rate	16
7.3.6	End-of-test condition	16

7.3.7	Test validity criteria	17
7.4	Test fire TF2A and TF2B -- Reduced smouldering (pyrolysis) wood fire	19
7.4.1	General	19
7.4.2	Fuel	19
7.4.3	Hotplate	19
7.4.4	Arrangement	19
7.4.5	Heating rate	20
7.4.6	End-of-test condition	20
7.4.7	Test validity criteria	20
7.5	Test fire TF3 -- Glowing smouldering cotton fire	21
7.5.1	General	21
7.5.2	Fuel	21
7.5.3	Arrangement	22
7.5.4	Ignition	22
7.5.5	End-of-test condition	22
7.5.6	Test validity criteria	23
7.6	Test fire TF3A and TF3B -- Reduced glowing smouldering cotton fire	24
7.6.1	General	24
7.6.2	Fuel	24
7.6.3	Arrangement	24
7.6.4	Ignition	25
7.6.5	End-of-test condition	25
7.6.6	Test validity criteria	25
7.7	Test fire TF4 -- Flaming plastics (polyurethane) fire	26
7.7.1	General	26
7.7.2	Fuel	26
7.7.3	Conditioning	26
7.7.4	Arrangement	26
7.7.5	Ignition	27
7.7.6	Method of ignition	27
7.7.7	End-of-test condition	27
7.7.8	Test validity criteria	27
7.8	Test fire TF5 -- Flaming liquid (n-heptane) fire	29
7.8.1	General	29
7.8.2	Fuel	29
7.8.3	Arrangement	29
7.8.4	Ignition	29
7.8.5	End-of-test condition	29
7.8.6	Test validity criteria	30
7.9	Test fire TF5A and TF5B -- Reduced flaming liquid (n-heptane) fire	32
7.9.1	General	32
7.9.2	Fuel	32
7.9.3	Arrangement	32
7.9.4	Ignition	33
7.9.5	End-of-test condition	33
7.9.6	Test validity criteria	33
7.10	Test fire TF6 -- Liquid (methylated spirit) fire	34
7.10.1	General	34
7.10.2	TF6 used for detectors with heat sensor	34
7.10.3	TF6 used for Point-type flame detectors	35
7.11	Test fire TF7 -- Slow smouldering (pyrolysis) wood fire	36
7.11.1	General	36
7.11.2	Fuel	36
7.11.3	Conditioning	36
7.11.4	Preparation	36
7.11.5	Hotplate	36
7.11.6	Arrangement	36
7.11.7	Heating rate	36
7.11.8	Test validity criteria	37
7.11.9	Variables	38
7.11.10	End-of-test condition	38

7.12	Test fire TF8 -- Low-temperature black-smoke liquid (decalin) fire	38
7.12.1	General	38
7.12.2	Fuel	38
7.12.3	Arrangement	38
7.12.4	Volume	38
7.12.5	Ignition	38
7.12.6	End-of-test condition	39
7.12.7	Test validity criteria	39
7.13	Test fire TF9 -- Deep-seated smouldering cotton fire	40
7.13.1	General	40
7.13.2	Fuel	40
7.13.3	Arrangement	41
7.13.4	Ignition	41
7.13.5	End-of-test condition	41
7.13.6	Test validity criteria	42
Annex A (informative) Information concerning the construction of the measuring ionization chamber		43
Annex B (informative) m value for different light beam lengths		45
Annex C (informative) y value		49
Bibliography		53