

ISO 21805:2023-02 (E)

Guidance and recommendations on design, selection and installation of vents to safeguard the structural integrity of enclosures protected by gaseous fire-extinguishing systems

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviated terms	2
5	Use and limitations	3
6	Safety	4
6.1	Structural safety	4
6.2	Personnel safety	4
7	System design -- Pressure-relief venting	4
7.1	General	4
7.2	Extinguishant characteristics	5
7.2.1	Positive and negative pressurization	5
7.2.2	Pressure graphs	5
7.3	Enclosure characteristics	6
7.4	Pressure-relief vent paths	6
7.5	Types of pressure-relief vents	7
7.5.1	General	7
7.5.2	Gravity vents	7
7.5.3	Counterweighted flap vent	7
7.5.4	Electrically-operated vents	8
7.5.5	Pneumatically-operated vent	8
7.5.6	Vent accessories	8
7.6	Pressure-relief vent characteristics	9
7.6.1	Vent efficiency	9
7.6.2	Minimum opening pressure	10
7.6.3	Minimum closing pressure	10
7.6.4	Fire rating	10
7.7	Vent location and mounting	10
7.7.1	Vent location	10
7.7.2	Vent mounting	11
7.8	Pressure-relief vent area calculations	12
7.8.1	Use of agent-specific formulae	12
7.8.2	Vent area requirement (non-liquefiable gases)	13
7.8.3	Vent area requirement carbon dioxide	16
7.8.4	Vent area requirements (liquefiable gases)	16
7.8.5	Leakage	22
7.9	Cascade venting calculations	22
7.9.1	Example calculation 3: Cascade venting calculations for IG-541 (peak discharge)	23
7.9.2	Cascade vent arrangements	24

7.9.3	Venting into adjacent enclosures	25
8	System design -- Post-discharge venting	27
9	Acceptance	27
10	Service and maintenance	27
	Annex A (informative) Development of agent-specific formulae for liquefiable gases	29
	Annex B (informative) Method for development of agent-specific formulae for liquefiable gases	34