

ISO 12239:2003-12 (E)

Fire detection and fire alarm systems - Smoke alarms

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | General requirements | 3 |
| 4.1 | Compliance | 3 |
| 4.2 | Alarm-condition aural indicator | 4 |
| 4.3 | Alarm-condition visual indicator -- Optional function | 4 |
| 4.4 | Mains-on visual indicator | 4 |
| 4.5 | Fault-condition visual indicator -- Optional function | 4 |
| 4.6 | Connection of external ancillary devices | 4 |
| 4.7 | Means of calibration | 4 |
| 4.8 | User-replaceable components | 4 |
| 4.9 | Primary power source | 4 |
| 4.10 | Standby power source | 5 |
| 4.11 | Electrical safety requirements | 6 |
| 4.12 | Test facility | 6 |
| 4.13 | Terminals for external conductors | 6 |
| 4.14 | Smoke-alarm signals | 6 |
| 4.15 | Battery removal indication | 7 |
| 4.16 | Battery connections | 7 |
| 4.17 | Protection against the ingress of foreign bodies | 7 |
| 4.18 | Interconnectable smoke alarms -- Optional function | 7 |
| 4.19 | Alarm-silence facility -- Optional function | 8 |
| 5 | Tests | 8 |
| 5.1 | General | 8 |
| 5.2 | Directional dependence | 10 |
| 5.3 | Initial sensitivity | 12 |
| 5.4 | Repeatability | 12 |
| 5.5 | Air movement | 12 |
| 5.6 | Dazzling | 13 |
| 5.7 | Dry heat (operational) | 14 |
| 5.8 | Cold (operational) | 14 |
| 5.9 | Damp heat (operational) | 15 |
| 5.10 | Sulfur dioxide (SO ₂) corrosion | 16 |
| 5.11 | Impact (operational) | 17 |
| 5.12 | Vibration, sinusoidal (operational) | 18 |
| 5.13 | Vibration, sinusoidal (endurance) | 19 |
| 5.14 | Extended temperature (operational) -- Optional function | 20 |
| 5.15 | Electromagnetic compatibility (EMC) immunity tests (operational) | 21 |
| 5.16 | Fire sensitivity | 21 |
| 5.17 | Battery-low condition | 23 |
| 5.18 | 85 dB(A) Sound output -- Optional function | 24 |
| 5.19 | 70 dB(A) Sound output -- Optional function | 24 |
| 5.20 | Sounder durability | 25 |

| | | |
|---|-------------------------------------|----|
| 5.21 | Interconnectable smoke alarms | 25 |
| 5.22 | Alarm-silence facility | 26 |
| 5.23 | Variation in supply voltage | 27 |
| 5.24 | Polarity reversal | 27 |
| 6 | Marking and data | 28 |
| 6.1 | Smoke-alarm marking | 28 |
| 6.2 | Packaging marking | 29 |
| 6.3 | Provision of information | 29 |
| 7 | Test report | 29 |
| Annex A (normative) Assessment of personal protection against various hazards | | 30 |
| Annex B (normative) Smoke tunnel for response-threshold value measurement | | 32 |
| Annex C (normative) Test aerosol for response threshold value measurements | | 33 |
| Annex D (normative) Smoke-measuring instruments | | 34 |
| Annex E (normative) Apparatus for dazzling test | | 38 |
| Annex F (normative) Apparatus for impact test | | 39 |
| Annex G (normative) Fire test room | | 41 |
| Annex H (normative) Smouldering pyrolysis wood fire (TF2) | | 43 |
| Annex I (normative) Glowing smouldering cotton fire (TF3) | | 46 |
| Annex J (normative) Flaming plastics (polyurethane) fire (TF4) | | 48 |
| Annex K (normative) Flaming liquid (n-heptane) fire (TF5) | | 50 |
| Annex L (informative) Information concerning the construction of the smoke tunnel | | 52 |
| Annex M (informative) Information concerning the construction of the measuring ionization chamber | | 54 |