

# ISO 7240-15:2004-03 (E)

## Fire detection and alarm systems - Part 15: Multisensor fire detectors

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>References .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions and abbreviations .....</b>	<b>2</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>3.2</b>	<b>Abbreviations .....</b>	<b>3</b>
<b>4</b>	<b>Functions .....</b>	<b>3</b>
<b>4.1</b>	<b>General .....</b>	<b>3</b>
<b>4.2</b>	<b>Optional functions .....</b>	<b>3</b>
<b>5</b>	<b>General requirements .....</b>	<b>4</b>
<b>5.1</b>	<b>Design considerations .....</b>	<b>4</b>
<b>5.2</b>	<b>Applicability .....</b>	<b>4</b>
<b>5.3</b>	<b>Individual alarm indication .....</b>	<b>4</b>
<b>5.4</b>	<b>Indication of other conditions .....</b>	<b>4</b>
<b>5.5</b>	<b>Calibration .....</b>	<b>4</b>
<b>5.6</b>	<b>Sensitivity adjustment .....</b>	<b>4</b>
<b>5.7</b>	<b>Sensitivity attenuation and signal disablement .....</b>	<b>5</b>
<b>5.8</b>	<b>Monitoring of detachable detectors .....</b>	<b>5</b>
<b>5.9</b>	<b>Drift compensation .....</b>	<b>5</b>
<b>5.10</b>	<b>Marking .....</b>	<b>5</b>
<b>5.11</b>	<b>Technical documentation .....</b>	<b>6</b>
<b>5.12</b>	<b>Manufacturer's declaration .....</b>	<b>6</b>
<b>5.13</b>	<b>Electrical requirements .....</b>	<b>6</b>
<b>5.14</b>	<b>Protection against ingress of foreign bodies .....</b>	<b>6</b>
<b>5.15</b>	<b>Requirements for software-controlled multisensor fire detectors .....</b>	<b>6</b>
<b>5.16</b>	<b>Storage of programs and data .....</b>	<b>8</b>
<b>5.17</b>	<b>Monitoring of memory contents -- Optional function .....</b>	<b>8</b>
<b>6</b>	<b>Tests .....</b>	<b>8</b>
<b>6.1</b>	<b>General .....</b>	<b>8</b>
<b>6.2</b>	<b>Repeatability .....</b>	<b>13</b>
<b>6.3</b>	<b>Directional dependence .....</b>	<b>13</b>
<b>6.4</b>	<b>Reproducibility .....</b>	<b>14</b>
<b>6.5</b>	<b>Variation in supply parameters (voltage) .....</b>	<b>14</b>
<b>6.6</b>	<b>Air movement .....</b>	<b>15</b>
<b>6.7</b>	<b>Dazzling .....</b>	<b>15</b>
<b>6.8</b>	<b>Dry heat (operational) .....</b>	<b>16</b>
<b>6.9</b>	<b>Cold (operational) .....</b>	<b>16</b>
<b>6.10</b>	<b>Damp heat, steady state (operational) .....</b>	<b>17</b>
<b>6.11</b>	<b>Damp heat, steady state (endurance) .....</b>	<b>18</b>
<b>6.12</b>	<b>Sulfur dioxide (SO<sub>2</sub>) corrosion (endurance) .....</b>	<b>19</b>
<b>6.13</b>	<b>Shock (operational) .....</b>	<b>20</b>
<b>6.14</b>	<b>Impact (operational) .....</b>	<b>21</b>
<b>6.15</b>	<b>Vibration, sinusoidal (operational) .....</b>	<b>22</b>
<b>6.16</b>	<b>Vibration, sinusoidal (endurance) .....</b>	<b>23</b>

6.17	Electromagnetic compatibility (EMC) .....	24
6.18	Fire sensitivity .....	24
6.19	Special requirements on detector sensitivity -- Optional function .....	26
7	Test report .....	26
Annex A (normative) Smoke tunnel .....		27
Annex B (informative) Construction of the measuring ionization chamber .....		32
Annex C (normative) Heat tunnel for temperature-response value measurements .....		36
Annex D (informative) Construction of the heat tunnel .....		37
Annex E (normative) Apparatus for the dazzling test .....		39
Annex F (normative) Apparatus for the impact test .....		40
Annex G (normative) Fire test room .....		42
Annex H (normative) Open cellulosic (wood) fire (TF1) .....		44
Annex I (normative) Smouldering (pyrolysis) wood fire (TF2) .....		46
Annex J (normative) Glowing smouldering cotton fire (TF3) .....		48
Annex K (normative) Flaming plastics (polyurethane) fire (TF4) .....		50
Annex L (normative) Flaming liquid (n-heptane) fire (TF5) .....		52
Annex M (normative) Liquid (methylated spirits) fire (TF6) .....		54
Annex N (normative) Low-temperature black-smoke liquid (decalin) fire (TF8) .....		56
Annex O (informative) Compensation for detector drift .....		58