

ISO 7240-6:2004-11 (E)

Fire detection and alarm systems - Part 6: Carbon monoxide fire detectors using electro-chemical cells

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms, definitions and symbols	2
4	General requirements	2
4.1	Compliance	2
4.2	Individual alarm indication	2
4.3	Connection of ancillary devices	3
4.4	Monitoring of detachable detectors	3
4.5	Manufacturer's adjustments	3
4.6	On-site adjustment of response behaviour	3
4.7	Rate-sensitive response behaviour	3
4.8	Marking	3
4.9	Data	4
4.10	Requirements for software controlled detectors	4
5	Tests	6
5.1	General	6
5.2	Repeatability	8
5.3	Directional dependence	9
5.4	Reproducibility	9
5.5	Cross sensitivity	10
5.6	Long-term stability	11
5.7	Saturation	11
5.8	Exposure to chemical agents associated with a fire	12
5.9	Variation in supply parameters	13
5.10	Air movement	13
5.11	Dry heat (operational)	14
5.12	Cold (operational)	15
5.13	Damp heat, steady state (operational)	16
5.14	Damp heat, steady state (endurance)	17
5.15	Sulfur dioxide (SO ₂) corrosion (endurance)	17
5.16	Shock (operational)	18
5.17	Impact (operational)	19
5.18	Vibration, sinusoidal (operational)	20
5.19	Vibration, sinusoidal (endurance)	22
5.20	Electromagnetic compatibility (EMC) immunity test (operational)	23
5.21	Fire sensitivity	23
6	Test report	25
Annex A (normative)	Gas test chamber for response threshold value and cross-sensitivity measurements	26
Annex B (informative)	Apparatus for impact test	27

Annex C (normative) Fire test room	29
Annex D (normative) Smouldering (pyrolysis) wood fire (TF2)	31
Annex E (normative) Glowing smouldering cotton fire (TF3)	33
Annex F (normative) Deep-seated smouldering cotton fire (TF9)	35
Annex G (informative) Information concerning the construction of the gas test chamber	37