

ISO 6182-2:2005-10 (E)

Fire protection - Automatic sprinkler systems - Part 2: Requirements and test methods for wet alarm valves, retard chambers and water motor alarms

| Contents | | Page |
|--------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Requirements | 3 |
| 4.1 | Nominal sizes | 3 |
| 4.2 | Connections | 3 |
| 4.3 | Rated working pressure | 3 |
| 4.4 | Bodies and covers | 4 |
| 4.5 | Strength | 4 |
| 4.6 | Access for maintenance | 4 |
| 4.7 | Components | 4 |
| 4.8 | Leakage | 5 |
| 4.9 | Non-metallic components (excluding gaskets, seals and other elastomeric parts) | 5 |
| 4.10 | Sealing assembly elements | 5 |
| 4.11 | Clearances | 6 |
| 4.12 | Hydraulic friction loss | 6 |
| 4.13 | Endurance | 8 |
| 4.14 | Operational performance | 9 |
| 4.15 | Drains | 9 |
| 4.16 | Alarms | 9 |
| 4.17 | Retard device | 10 |
| 4.18 | Water motor alarms | 11 |
| 5 | Production testing and quality control | 12 |
| 6 | Tests | 12 |
| 6.1 | Samples | 12 |
| 6.2 | Spring and diaphragm test | 12 |
| 6.3 | Sealing element tests | 12 |
| 6.4 | Warm water aging test for non-metallic components (excluding gaskets and seals and other elastomeric parts) | 14 |
| 6.5 | Air aging test for non-metallic components (excluding gaskets and seals and other elastomeric parts) | 14 |
| 6.6 | Endurance test | 15 |
| 6.7 | Hydraulic friction loss test | 15 |
| 6.8 | Valve leakage and deformation tests | 15 |
| 6.9 | Body strength test | 16 |
| 6.10 | Fire exposure test | 16 |
| 6.11 | Operational test | 17 |
| 6.12 | Water motor alarm tests | 19 |
| 6.13 | Retard chamber tests | 19 |
| 6.14 | Salt mist corrosion test | 20 |
| 7 | Marking | 20 |
| 8 | Instruction charts and trim | 21 |
| Bibliography | | 22 |