

ISO 7240-12:2006-02 (E)

Fire detection and alarm systems - Part 12: Line type smoke detectors using a transmitted optical beam

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	General requirements	3
4.1	Compliance	3
4.2	Individual alarm indication	3
4.3	Connection of ancillary devices	3
4.4	Monitoring of detachable detectors and connections	3
4.5	Manufacturer's adjustments	3
4.6	On-site adjustment of response threshold value	4
4.7	Protection of optical components	4
4.8	Limit of compensation	4
4.9	Marking	4
4.10	Data	5
4.11	Requirements for software-controlled detectors	5
4.12	Fault signalling	6
5	Test methods	6
5.1	General	6
5.2	Reproducibility	8
5.3	Repeatability	9
5.4	Directional dependence	10
5.5	Variation of supply parameters	11
5.6	Rapid changes in attenuation	11
5.7	Slow changes in attenuation	12
5.8	Optical path length dependence	12
5.9	Fire sensitivity	13
5.10	Stray light	15
5.11	Dry heat (operational)	16
5.12	Cold (operational)	17
5.13	Damp heat, steady state (operational)	18
5.14	Damp heat, steady state (endurance)	19
5.15	Vibration, sinusoidal (endurance)	20
5.16	Electromagnetic compatibility (EMC), immunity tests (operational)	21
5.17	Sulfur dioxide, SO ₂ , corrosion (endurance)	21
5.18	Impact (operational)	22
6	Test report	23
Annex A (informative)	Compensation for detector drift	24
Annex B (normative)	Bench for response threshold value measurements	29
Annex C (normative)	Fire test room	31

Annex D (normative) Smouldering pyrolysis wood fire (TF2)	33
Annex E (normative) Glowing smouldering cotton fire (TF3)	35
Annex F (normative) Flaming plastics (polyurethane) fire (TF4)	37
Annex G (normative) Flaming liquid (n-heptane) fire (TF5)	39
Annex H (normative) Smoke-measuring instruments	40
Annex I (normative) Apparatus for stray light	43
Annex J (informative) Information concerning the construction of the measuring ionization chamber	45